

Roji Sheet


Collection	Terasu	
Style Number	0798V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fiberglass	
class	Type I, Grade 1, Class B	
Backing Class	4-ply fused backing system	
Finish	ExoGuard®	
	U.s.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.087 in	2.2 mm
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
Area Per Roll	50.75 sy/roll	42.43 sq m/roll
Weight Per Roll	337.7 lbs	153.18 kg



Recommended Installation Method



Coordinating Products

Sheet: Tatami Sheet, Reed Sheet  
Carpet Tile: Botan Tile, Hana Tile, Kusa Tile  
Broadloom: Botan, Hana, Kusa

performance + testing

residual indentation (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg CO <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   3rd Party Certified
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>FloorScore® Certified</b>
EQ Credit: Low Emitting Materials	
Option 1: Product Category Calculations	







[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Pebble 96114 Weldrod 07332	Tea Garden 96216 Weldrod 07332	Zen 96515 Weldrod 01203	Stroll 96535 Weldrod 02012	Stepping Stone 96700 Weldrod 12155	Pagoda 96710 Weldrod 05244

