

Roji Sheet

수집	Terasu	
스타일 번호	0798V	
응접봉 스타일 번호	353VS	
구성	유리 섬유가있는 상업용 이중 시트	
수업	Type I, Grade 1, Class B	
후원 수업	4-플라이 퓨즈 장착 바닥면 시스템	
끝	ExoGuard®	
	미국	미터법
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.087 in	2.2 mm
권장 접착제	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

포장

실제 롤 크기	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
롤당 면적	50.75 sy/roll	42.43 sq m/roll
롤 당 무게	337.7 lbs	153.18 kg



권장 설치 방법



코디네이팅 제품

Sheet: Tatami Sheet, Reed Sheet
Carpet Tile: Botan Tile, Hana Tile, Kusa Tile
Broadloom: Botan, Hana, Kusa

공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
내열성 (ASTM F1514)	Passes
내광성 (ASTM F1515)	Passes
화학 물질에 대한 내성 (ASTM F925)	Passes
복사 패널 (ASTM E648)	Passes, Class I
마찰 계수 (ASTM D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

15년 상용 제한
Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)
Embodied Carbon (Cradle to Gate)
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득
9.4 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 타사 인증 획득
Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)
EQ 크레딧 : 저 발광 재료
옵션 1 : 제품 범주 계산

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore® Certified







Installation Guidelines
Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Pebble 96114 Weldrod 07332	Tea Garden 96216 Weldrod 07332	Zen 96515 Weldrod 01203	Stroll 96535 Weldrod 02012	Stepping Stone 96700 Weldrod 12155	Pagoda 96710 Weldrod 05244

