

Terrain 8 Mil

| | | |
|----------|------------------------|--------------------------|
| コレクション | Terrain | |
| スタイルナンバー | 0655V | |
| クラス | Class III, Type B | |
| 仕上げ | ExoGuard® | |
| | 米国 | メートル法 |
| 公称寸法 | 6 in w x 48 in l | 15 cm w x 122 cm l |
| 実際の寸法 | 5.96 in w x 48.00 in l | 15.14 cm w x 121.92 cm l |
| 摩耗層の厚さ | 8 mil (0.008 in) | 0.2 mm |
| 製品全体の厚さ | 0.079 in | 2 mm |
| インストール | Direct Glue | |

包装

| | | |
|------------|-------------|-----------|
| ボックスあたりの個数 | 27 pcs | |
| ボックスあたりの面積 | 53.63 sq ft | 4.98 sq m |
| ボックスあたりの重量 | 39 lbs | 17.69 kg |

コーディネート商品

None: Terrain 12

パフォーマンス + テスト

| | | |
|-----------------------|---|--|
| 静荷重 (ASTM F970) | Passes (Modified), *1500 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| 残留圧痕 (ASTM F1914) | Passes | |
| 耐熱性 (ASTM F1514) | Passes | |
| 耐光性 (ASTM F1515) | Passes | |
| 耐薬品性 (ASTM F925) | Passes | |
| 放射パネル (ASTM E648) | Passes, Class I | |
| 摩擦係数(ASTM D2407、滑り抵抗) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

5 Year Light Commercial Limited Warranty

属性+認定

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® 認証取得 |
| Climate Impact | |
| Environmental Product Declaration (EPD) | ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得 |
| Embodied Carbon (Cradle to Gate) | 7.04 Kg Co ₂ /M ² |
| Life-Cycle Carbon Emissions**** | Low Embodied Carbon |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | CE Marking (EN 14041) 第三者認証取得 |
| | Country of Origin 中国 |

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | FloorScore Certificate |

グリーンリード貢献クレジット

| | |
|--|---|
| MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート | Health Product Declaration (HPD) 100 Ppm Disclosure |
| MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQクレジット：低排出材料 オプション1：製品カテゴリの計算 | FloorScore® Certified |

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

