


Terrain 8 Mil

수집	Terrain	
스타일 번호	0655V	
구성	경량 상용 고급 비닐타일	
수업	Class III, Type B	
끝	ExoGuard®	
	미국	미터법
공칭 치수	6 in w x 48 in l	15 cm w x 122 cm l
실제 치수	5.96 in w x 48.00 in l	15.14 cm w x 121.92 cm l
마모 층 두께	8 mil (0.008 in)	0.2 mm
전체 제품 두께	0.079 in	2 mm
가장자리 프로필	사각형 모서리	
Installation Type	Dry Back	
설치	Direct Glue	
권장 접착제	S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

포장

상자 당 조각	27 pcs	
상자 당 면적	53.63 sq ft	4.98 sq m
상자 당 무게	39 lbs	17.69 kg

권장 설치 방법



코디네이팅 제품

None: Terrain 12

공연 + 테스트

정적 하중 (Astm F970)	Passes (Modified), *1500 lbs	이 테스트는 다양한 스타일과 구성의 상대적인 속성을 비교하기위한 것입니다. 결과는 실험실 테스트를 기반으로하며 비교 목적으로 사용됩니다. 실제 하중 한계는 다를 수 있습니다.
잔차 들어 쓰기 (Astm F1914)	Passes	
내열성 (Astm F1514)	Passes	
내광성 (Astm F1515)	Passes	
화학 물질에 대한 내성 (Astm F925)	Passes	
복사 패널 (Astm E648)	Passes, Class I	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes
마찰 계수(astm D2407, 미끄러짐 저항)		

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

5년 상용 제한

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득  
7.04 Kg Co<sub>2</sub>/M<sup>2</sup>  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 타사 인증 획득  
Country of Origin | Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축  
재료 성분-옵션 1 : 재료 성분보고

Health Product Declaration (HPD) | 100 Ppm Disclosure

MR 크레딧 : 제품 공개 및 최적화 구축  
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

EQ 크레딧 : 저 발광 재료  
옵션 1 : 제품 범주 계산

FloorScore Certified

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Shade 00548  
V2 - Slight Variation



Root 00558  
V4 - Substantial Variation



Timber 00590  
V3 - Moderate Variation



Nest 00755  
V3 - Moderate Variation



Echo 00766  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

