

Solitude

| | | |
|----------------------|--|--------------------------|
| Collection | Solitude | |
| Style Number | 0648V | |
| Construction | Heavy Commercial Luxury Vinyl Tile With Fiberglass | |
| Class / ASTM F1700 | Class III, Type B | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Nominal Dimensions | 6 in w x 48 in l | 15 cm w x 122 cm l |
| Actual Dimensions | 6.00 in w x 48.00 in l | 15.24 cm w x 121.92 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Thickness | 0.197 in | 5 mm |
| Edge Profile | Squared Edge | |
| Installation Type | Dry Back | |
| Installation | Direct Glue | |
| Recommended Adhesive | S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |



Packaging

| | | |
|-------------------|----------|-----------|
| Pieces Per Carton | 10 pcs | |
| Area Per Carton | 20 sq ft | 1.86 sq m |
| Weight Per Carton | 35.1 lbs | 15.92 kg |

Recommended Installation Method



Performance + Testing

| | | |
|---|---|--|
| Static Load (ASTM F970) | Passes (Modified), *1500 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| Residual Indentation (ASTM F1914) | Passes | |
| Resistance to Heat (ASTM F1514) | Passes | |
| Resistance to Light (ASTM F1515) | Passes | |
| Resistance to Chemicals (ASTM F925) | Passes | |
| Smoke Density (ASTM E662, Flaming Mode) | Passes | Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. |
| Radiant Panel (ASTM E648) | Passes, Class I | |
| coefficient of friction (ASTM D2407, slip resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | |

Warranties

[15 Year Commercial Limited](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 11.59 Kg CO ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | CE Marking (EN 14041) 3rd Party Certified |
| | Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|--|---|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | FloorScore Certificate |

Green Leed Contribution Credit

| | |
|---|--|
| MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting | Health Product Declaration (HPD) 100 Ppm Disclosure |
| MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQ Credit: Low Emitting Materials Option 1: Product Category Calculations | FloorScore® Certified |





[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Cocoa 48103 LRV 20.8 L* 52.74 V2 - Slight Variation | Cottonwood 48120 LRV 42.5 L* 71.25 V2 - Slight Variation | Natural 48250 LRV 28.7 L* 60.55 V2 - Slight Variation | Smoke 48506 LRV 26.3 L* 58.3 V2 - Slight Variation | Fawn 48516 LRV 25.7 L* 57.74 V2 - Slight Variation | Urban Ash 48540 V2 - Slight Variation |
|  |  |  |  |  |  |
| Char 48549 LRV 7.2 L* 32.3 V2 - Slight Variation | Pewter 48595 LRV 22.6 L* 54.67 V2 - Slight Variation | French Grey 48599 LRV 20.8 L* 52.69 V3 - Moderate Variation | Mink 48720 LRV 16.8 L* 47.99 V3 - Moderate Variation | Woodland 48760 LRV 17.2 L* 48.51 V2 - Slight Variation | Umber 48761 LRV 11 L* 39.65 V2 - Slight Variation |

 **Quick Ship** Immediately (In Stock Australia)

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

| | | | |
|---|--|---|---|
| V1  | V2  | V3  | V4  |
| Uniform Appearance | Slight Variation | Moderate Variation | Substantial Variation |

