

Cut

| | | |
|-------------------|--|-------------------------|
| 수집 | Natural Choreography | |
| 스타일 번호 | 0922V | |
| 구성 | 섬유 유리를 가진 헤비급 상업적인 고급 비닐 도와 | |
| 수업 | Class III, Type B | |
| 끝 | ExoGuard® | |
| | 미국 | 미터법 |
| 공칭 치수 | 18 in w x 18 in l | 46 cm w x 46 cm l |
| 실제 치수 | 18.00 in w x 18.00 in l | 45.72 cm w x 45.72 cm l |
| 마모 층 두께 | 20 mil (0.02 in) | 0.51 mm |
| 전체 제품 두께 | 0.197 in | 5 mm |
| 가장자리 프로파일 | 사각형 모서리 | |
| Installation Type | Dry Back | |
| 설치 | Direct Glue | |
| 권장 접착제 | S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

포장

| | | |
|---------|------------|-----------|
| 상자 당 조각 | 10 pcs | |
| 상자 당 면적 | 22.5 sq ft | 2.09 sq m |
| 상자 당 무게 | 30.86 lbs | 14 kg |



권장 설치 방법



공연 + 테스트

| | |
|--|---|
| 내열성 (Astm F1514) | Passes |
| 내광성 (Astm F1515) | Passes |
| 화학 물질에 대한 내성 (Astm F925) | Passes |
| 복사 패널 (Astm E648) | Passes, Class I |
| 마찰 계수 (astm D2407, 미끄러짐 저항) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. | |

보증

15년 상용 제한
Commercial 15 Year Underbed Bond Warranty.

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)
Embodied Carbon (Cradle to Gate)
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득
7.31 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축
재료 성분-옵션 1 : 재료 성분보고
MR 크레딧 : 제품 공개 및 최적화 구축
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)
EQ 크레딧 : 저 발광 재료
옵션 1 : 제품 범주 계산

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified







Installation Guidelines
Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Ecru 22103 LRV 29.7 L* 61.38 V2 - Slight Variation | Mushroom 22155 LRV 21.7 L* 53.72 V2 - Slight Variation | Talc 22174 LRV 24.7 L* 56.74 V2 - Slight Variation | Honey 22280 LRV 16.1 L* 47.13 V2 - Slight Variation | Charcoal 22549 LRV 11.3 L* 40.13 V2 - Slight Variation | Ash 22599 LRV 16.1 L* 47.04 V2 - Slight Variation |



Cacao 22704
LRV 8.4 | L* 34.77
V2 - Slight Variation



Sienna 22760
LRV 8.8 | L* 35.66
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

