


Concrete

수집	Concrete + Composed		
스타일 번호	094UV		
구성	코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(SPC)		
수업	Class III, Type B		
첨부 된 밀 갈개	코르크		
끝	ExoGuard®		
공칭 치수	미국	미터법	
	19 in w x 24 in l	47 cm w x 61 cm l	
	실제 치수	18.50 in w x 24.02 in l	46.99 cm w x 61.01 cm l
	마모 층 두께	20 mil (0.02 in)	0.51 mm
	전체 제품 두께	0.217 in	5.5 mm
가장자리 프로파일	마이크로 베벨		
Installation Type	Click		
설치	Floating Or Direct Glue		
권장 접착제	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL		

포장

상자 당 조각	10 pcs	
상자 당 면적	30.86 sq ft	2.87 sq m
상자 당 무게	52.91 lbs	24 kg

권장 설치 방법



코디네이팅 제품

COREtec: Composed

공연 + 테스트

잔차 들어 쓰기 (Astm F1914)	Passes
내열성 (Astm F1514)	Passes
내광성 (Astm F1515)	Passes
복사 패널 (Astm E648)	Passes, Class I
마찰 계수(astm D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

15년 상용 제한

## 속성 + 인증

## Health &amp; Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | 인증

## Climate Impact

Environmental Product Declaration (EPD)  
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득  
0% (Pre-Consumer 0% | Post-Consumer 0%)

## Global Product Assessment

CE Marking (EN 14041) | 타사 인증 획득  
Country of Origin | Imported

## 녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축  
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)

EQ 크레딧 : 저 발광 재료  
옵션 1 : 제품 범주 계산

Installation Guidelines

Maintenance Guidelines

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**

**FloorScore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways



Misty Quartz 03501  
LRV 51.2 | L\* 76.8



Tempered Concre 03502  
LRV 28.1 | L\* 59.95



Rugged Platinum 03503  
LRV 23.2 | L\* 55.33



Forged Concrete 03507  
LRV 22.1 | L\* 54.13



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
November 21, 2024

2 of 2