


Concrete

수집	Concrete + Composed	
스타일 번호	094UV	
구성	코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(SPC)	
수업	Class III, Type B	
첨부 된 밀 갈개	코르크	
끝	ExoGuard®	
	미국	미터법
공칭 치수	19 in w x 24 in l	47 cm w x 61 cm l
실제 치수	18.50 in w x 24.02 in l	46.99 cm w x 61.01 cm l
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.217 in	5.5 mm
가장자리 프로파일	마이크로 베벨	
Installation Type	Click	
설치	Floating Or Direct Glue	
권장 접착제	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

포장

상자 당 조각	10 pcs	
상자 당 면적	30.86 sq ft	2.87 sq m
상자 당 무게	52.91 lbs	24 kg

권장 설치 방법



코디네이팅 제품

COREtec: Composed

공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	Passes
내열성 (ASTM F1514)	Passes
내광성 (ASTM F1515)	Passes
복사 패널 (ASTM E648)	Passes, Class I
마찰 계수(ASTM D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 타사 인증 획득
Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
Greenguard Gold Certificate

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)
EQ 크레딧 : 저 발광 재료
옵션 1 : 제품 범주 계산

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore® Certified

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Misty Quartz 03501
LRV 51.2 | L* 76.8



Tempered Concre 03502
LRV 28.1 | L* 59.95



Rugged Platinum 03503
LRV 23.2 | L* 55.33



Forged Concrete 03507
LRV 22.1 | L* 54.13

