

Composed

Colección	Concrete + Composed	
Número De Estilo	098UV	
Construcción	SPC Multicapa Con Base De Corcho Adjunta	
clase	Class III, Type B	
Manta Inferior Adicional	Corcho	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensiones Reales	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.217 in	5.5 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

Embalaje

Piezas Por Caja	12 pcs	
Área Por Caja	28.68 sq ft	2.66 sq m
Peso Por Caja	49.82 lbs	22.6 kg

Método De Instalación Recomendado



Productos Que Combinan

COREtec: Concrete

Desempeño + Pruebas

Margen Adicional Residual (Astm F1914)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Panel Radiante (Astm E648)	Passes, Class I
Coeficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Total Recycled Content

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado Tercerizado  
Country of Origin | China

Contribución Para Créditos Leed

- Crédito MR: Divulgación y optimización de productos de construcción
- Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)
- Crédito EQ: Materiales de baja emisión
- Opción 1: Cálculos de categoría de producto

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

- Installation Guidelines
- Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Orchard 00103  
LRV 24.4 | L\* 56.52



Pale 00111  
LRV 51.8 | L\* 77.18



Cascade 00120  
LRV 41.4 | L\* 70.47



Grand Teton 00506  
LRV 33.9 | L\* 64.92



Stony Oak 00516  
LRV 25.8 | L\* 57.86



Buckeye 00710  
LRV 12.5 | L\* 42.02



Spice 00720  
LRV 18.2 | L\* 49.75



Bison 00751  
LRV 10.3 | L\* 38.36



Chalet 00755  
LRV 22.4 | L\* 54.46



Landscape 00760  
LRV 18.6 | L\* 50.2

