


Composed

수집	Concrete + Composed	
스타일 번호	098UV	
구성	코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(SPC)	
수업	Class III, Type B	
첨부 된 밀 갈개	코르크	
끝	ExoGuard®	
	미국	미터법
공칭 치수	7 in w x 48 in l	18 cm w x 122 cm l
실제 치수	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.217 in	5.5 mm
가장자리 프로파일	마이크로 베벨	
Installation Type	Click	
설치	Floating Or Direct Glue	
권장 접착제	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

포장

상자 당 조각	12 pcs	
상자 당 면적	28.68 sq ft	2.66 sq m
상자 당 무게	49.82 lbs	22.6 kg

권장 설치 방법



코디네이팅 제품

COREtec: Concrete

공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	Passes
내열성 (ASTM F1514)	Passes
내광성 (ASTM F1515)	Passes
복사 패널 (ASTM E648)	Passes, Class I
마찰 계수(ASTM D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

속성 + 인증

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® 인증
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 타사 인증 획득
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard Gold Certificate

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)	FloorScore® Certified
EQ 크레딧 : 저 발광 재료	
옵션 1 : 제품 범주 계산	
Installation Guidelines	
Maintenance Guidelines	

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Orchard 00103 LRV 24.4 L* 56.52	Pale 00111 LRV 51.8 L* 77.18	Cascade 00120 LRV 41.4 L* 70.47	Grand Teton 00506 LRV 33.9 L* 64.92	Stony Oak 00516 LRV 25.8 L* 57.86	Buckeye 00710 LRV 12.5 L* 42.02
					
Spice 00720 LRV 18.2 L* 49.75	Bison 00751 LRV 10.3 L* 38.36	Chalet 00755 LRV 22.4 L* 54.46	Landscape 00760 LRV 18.6 L* 50.2		

