

Composed


Coleção	Concrete + Composed	
Número Do Produto	098UV	
Construção	SPC Multicamada Com Base De Cortiça Anexada	
classe	Class III, Type B	
Manta Inferior Adicional	Cortiça	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 122 cm l
Dimensões Reais	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.217 in	5.5 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating Or Direct Glue	
Adesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Simi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	



Empacotamento

Peças Por Caixa	12 pcs	
Área Por Caixa	28.68 sq ft	2.66 sq m
Peso Por Caixa	49.82 lbs	22.6 kg

Método De Instalação Recomendado



Produtos Coordenados

COREtec: Concrete

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Coefficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

15 Anos Comercial Limitada

Atributos + Certificações

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado

CE Marking (EN 14041) | Certificado 3rd Party

Country of Origin | China

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Crédito de EQ: Materiais de baixa emissão
Opção 1: cálculos de categoria de produto

FloorScore Certified

Installation Guidelines

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Orchard 00103
LRV 24.4



Pale 00111
LRV 51.8



Cascade 00120
LRV 41.4



Grand Teton 00506
LRV 33.9



Stony Oak 00516
LRV 25.8



Buckeye 00710
LRV 12.5



Spice 00720
LRV 18.2



Bison 00751
LRV 10.3



Chalet 00755
LRV 22.4



Landscape 00760
LRV 18.6

