


Composed

系列	Concrete + Composed	
款型编号	098UV	
结构	软木底多层复合	
类型	Class III, Type B	
附加垫层	软木	
表面处理	ExoGuard®	
	美国	尺寸标准
公称尺寸	7 in w x 48 in l	18 cm w x 122 cm l
实际尺寸	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
耐磨层厚度	20 mil (0.02 in)	0.51 mm
产品整体厚度	0.217 in	5.5 mm
边缘轮廓	微斜角	
Installation Type	Click	
安装方式	Floating Or Direct Glue	
胶粘剂建议	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

包装

每盒件数	12 pcs	
每箱面积	28.68 sq ft	2.66 sq m
每箱重量	49.82 lbs	22.6 kg

铺装建议



性能 + 测试

残余压痕 (ASTM F1914)	Passes
耐热性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
辐射板 (ASTM E648)	Passes, Class I
摩擦系数 (ASTM D2407, 防滑性)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

质保

15年商用有限质保

属性+认证

Health & Wellbeing	Health Product Declaration (HPD)   1000 ppm Disclosure FloorScore®   认证
Climate Impact	通过ISO 14025、EN 15804和ISO 21930 : 2017等第三方认证 11.8 Kg CO <sub>2</sub> /M <sup>2</sup> 0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   第三方认证 Country of Origin   中国



WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>Greenguard Gold Certificate</b>

绿色leed贡献信用

MR Credit : 建立产品披露和优化 环境产品声明-选项1 : 环境产品声明 (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
EQ信用 : 低排放材料 选项1 : 产品类别计算	<b>FloorScore® Certified</b>
<a href="#">Installation Guidelines</a> <a href="#">Maintenance Guidelines</a>	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

Available Colorways

					
Orchard 00103 LRV 24.4   L* 56.52	Pale 00111 LRV 51.8   L* 77.18	Cascade 00120 LRV 41.4   L* 70.47	Grand Teton 00506 LRV 33.9   L* 64.92	Stony Oak 00516 LRV 25.8   L* 57.86	Buckeye 00710 LRV 12.5   L* 42.02

			
Spice 00720 LRV 18.2   L* 49.75	Bison 00751 LRV 10.3   L* 38.36	Chalet 00755 LRV 22.4   L* 54.46	Landscape 00760 LRV 18.6   L* 50.2

