

Composed


Collection	Concrete + Composed	
Style Number	098UV	
Aspect class	Rigid Core Lvt Class III, Type B	
Attached Underlayment	Cork	
Finish	ExoGuard®	
	Metric	U.S.
Nominal Dimensions	18 cm w x 122 cm l	7 in w x 48 in l
Actual Dimensions	18.21 cm w x 122.00 cm l	7.17 in w x 48.03 in l
Wear Layer Thickness	0.51 mm	20 mil (0.02 in)
Overall Product Thickness	5.5 mm	0.217 in
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Recommended Adhesive	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

Packaging

Pieces Per Box	12 pcs	
Area Per Box	2.66 sq m	28.68 sq ft
Weight Per Box	22.6 kg	49.82 lbs



Recommended Installation Method



Coordinating Products

COREtec: Concrete

Performance + Testing

Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Coefficient of Friction (ASTM D2047, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Material Health & Environmental Certifications

Health Product Declaration (HPD)	1000 ppm Disclosure
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore®	Certified
CE Marking (EN 14041)	3rd Party Certified
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Country of Origin	China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	Greenguard Gold Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Light Reflectance Value

					
Orchard 00103 LRV 24.4	Pale 00111 LRV 51.8	Cascade 00120 LRV 41.4	Grand Teton 00506 LRV 33.9	Stony Oak 00516 LRV 25.8	Buckeye 00710 LRV 12.5
					
Spice 00720 LRV 18.2	Bison 00751 LRV 10.3	Chalet 00755 LRV 22.4	Landscape 00760 LRV 18.6		