

## Composed


Collection	<b>Concrete + Composed</b>	
Numéro De Style	<b>098UV</b>	
Construction	<b>SPC Multicouche Avec Sous-Couche EN Liège Attachée</b>	
classe	<b>Class III, Type B</b>	
Endos Intégrée	<b>Liège</b>	
Finition	<b>ExoGuard®</b>	
	Impérial	Métrique
Dimensions Nominales	<b>7 in w x 48 in l</b>	<b>18 cm w x 122 cm l</b>
Dimensions Réelles	<b>7.17 in w x 48.03 in l</b>	<b>18.21 cm w x 122.00 cm l</b>
Épaisseur De La Couche d'Usure	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Épaisseur Générale Du Produit	<b>0.217 in</b>	<b>5.5 mm</b>
Profil Du Bord	<b>Micro-Biseau</b>	
Installation Type	<b>Click</b>	
Installation	<b>Floating Or Direct Glue</b>	
Adhésif Recommandé	<b>4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL</b>	



### Emballage

Pièces Par Carton	<b>12 pcs</b>	
Surface Par Carton	<b>28.68 sq ft</b>	<b>2.66 sq m</b>
Poids Par Carton	<b>49.82 lbs</b>	<b>22.6 kg</b>

### Méthodes d'Installation Conseillées



### Coordination Des Produits

COREtec: Concrete

### Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	<b>Passes</b>
Résistance À La Chaleur (Astm F1514)	<b>Passes</b>
Résistance À La Lumière (Astm F1515)	<b>Passes</b>
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)	<b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé

CE Marking (EN 14041) | Certifié Par Un Tiers

Country of Origin | Imported

Contribution Au Certificat Vert Lead

« Crédit MR : Divulgateion et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

[Maintenance Guidelines](#)

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**

**FloorScore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Orchard 00103 LRV 24.4	Pale 00111 LRV 51.8	Cascade 00120 LRV 41.4	Grand Teton 00506 LRV 33.9	Stony Oak 00516 LRV 25.8	Buckeye 00710 LRV 12.5
					
Spice 00720 LRV 18.2	Bison 00751 LRV 10.3	Chalet 00755 LRV 22.4	Landscape 00760 LRV 18.6		

