

Vitality Sheet


| | | |
|--------------------------|---|--------|
| Collection | Vitality | |
| Style Number | 0873V | |
| Welding Rod Style Number | 353VS | |
| Construction | Commercial Homogeneous Sheet | |
| Class / ASTM F1913 | | |
| Finish | ExoGuard® | |
| | U.S. | Metric |
| Overall Thickness | 0.079 in | 2 mm |
| Installation Type | Dry Back | |
| Recommended Adhesive | S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|------------------|------------------------|----------------------|
| Actual Roll Size | 6.58 ft w x 65.94 ft l | 2.01 m w x 20.10 m l |
| Area per Roll | 47.84 sy/roll | 40 sq m/roll |
| Weight per Roll | 284 lbs | 128.82 kg |



Recommended Installation Method



Reverse

Coordinating Products

Sheet: Vitality Tones, Vitality Hues

Performance + Testing

| | | |
|---|---|--|
| Static Load (ASTM F970) | Passes (Modified), *2000 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| Residual Indentation (ASTM F1914) | Passes | |
| Flexibility (ASTM F137) | Passes | |
| Resistance to Heat (ASTM F1514) | Passes | |
| Resistance to Light (ASTM F1515) | Passes | |
| Resistance to Chemicals (ASTM F925) | Passes | |
| Radiant Panel (ASTM E648) | Passes, Class I | |
| Coefficient of Friction (ASTM D2047, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited Warranty](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

6.91 Kg CO₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 3rd Party Certified
Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions
Part 1: (C): Restrict Asbestos Precondition

X08 Hazardous Material Reduction
Part 1: Limit Hazardous Materials Optimization

X10 Volatile Compound Reduction
Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

X10 Volatile Compound Reduction
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

X11 Long Term Emissions Control
Part 2: Flooring Optimization

Absence of Asbestos

Absence of Heavy Metals

Absence of Halogenated Flame Retardants

Ortho-Phthalates

FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Rejuvenate 73100 LRV 73.1 L* 88.49 Weldrod 05201 | Inspire 73104 Weldrod 05202 | Delight 73110 Weldrod 05206 | Radiate 73112 Weldrod 05207 | Uplift 73120 Weldrod 05226 | Heal 73144 Weldrod 05237 |
|  |  |  |  |  |  |
| Warmth 73155 Weldrod 05209 | Zest 73201 Weldrod 05241 | Flourish 73325 Weldrod 05242 | Nourish 73370 Weldrod 05245 | Benefit 73415 Weldrod 05232 | Soothe 73447 Weldrod 05239 |
|  |  |  |  |  |  |
| Exhilarate 73485 Weldrod 05240 | Elevate 73505 Weldrod 05205 | Excite 73515 Weldrod 05203 | Restore 73518 Weldrod 05204 | Strength 73530 Weldrod 05225 | Invigorate 73535 Weldrod 05238 |
|  |  |  |  |  |  |
| Energy 73675 Weldrod 05219 | Thrive 73700 Weldrod 05243 | Abundance 73740 Weldrod 05230 | Comfort 73755 Weldrod 05228 | Balance 73761 Weldrod 05244 | Robust 73855 Weldrod 05220 |



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company
November 21, 2024