

Vitality Sheet


Collection	Vitality	
Style Number	0873V	
Welding Rod Style Number	353VS	
Construction	Commercial Homogeneous Sheet	
Class / ASTM F1913		
Finish	ExoGuard®	
	U.s.	Metric
Overall Thickness	0.079 in	2 mm
Installation Type	Dry Back	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.58 ft w x 65.94 ft l	2.01 m w x 20.10 m l
Area Per Roll	47.84 sy/roll	40 sq m/roll
Weight Per Roll	284 lbs	128.82 kg



Recommended Installation Method



Performance + Testing

Residual Indentation (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- 15 Year Commercial Limited
- Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	6.91 Kg Co <sub>2</sub> /M <sup>2</sup>
Life-Cycle Carbon Emissions	Low Embodied Carbon
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   3rd Party Certified
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>FloorScore® Certified</b>
EQ Credit: Low Emitting Materials	
Option 1: Product Category Calculations	

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways

					
Rejuvenate 73100 LRV 73.1   L* 88.49 Weldrod 05201	Inspire 73104 Weldrod 05202	Delight 73110 Weldrod 05206	Radiate 73112 Weldrod 05207	Uplift 73120 Weldrod 05226	Heal 73144 Weldrod 05237
					
Warmth 73155 Weldrod 05209	Zest 73201 Weldrod 05241	Flourish 73325 Weldrod 05242	Nourish 73370 Weldrod 05245	Benefit 73415 Weldrod 05232	Soothe 73447 Weldrod 05239
					
Exhilarate 73485 Weldrod 05240	Elevate 73505 Weldrod 05205	Excite 73515 Weldrod 05203	Restore 73518 Weldrod 05204	Strength 73530 Weldrod 05225	Invigorate 73535 Weldrod 05238
					
Energy 73675 Weldrod 05219	Thrive 73700 Weldrod 05243	Abundance 73740 Weldrod 05230	Comfort 73755 Weldrod 05228	Balance 73761 Weldrod 05244	Robust 73855 Weldrod 05220

