

Vitality Sheet


Collection	Vitality	
Style Number	0873V	
Welding Rod Style Number	353VS	
Construction class	Commercial Homogeneous Sheet	
Finish	ExoGuard®	
	U.s.	Metric
Overall Product Thickness	0.079 in	2 mm
Installation Type	Dry Back	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.58 ft w x 65.94 ft l	2.01 m w x 20.10 m l
Area Per Roll	47.84 sy/roll	40 sq m/roll
Weight Per Roll	284 lbs	128.82 kg



Recommended Installation Method



Coordinating Products

Sheet: Vitality Tones, Vitality Hues

performance + testing

residual indentation (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)  
  
Embodied Carbon (Cradle to Gate)  
Life-Cycle Carbon Emissions  
Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
6.91 Kg CO<sub>2</sub>/M<sup>2</sup>  
Low Embodied Carbon  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 3rd Party Certified  
Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt  
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt  
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos  
Absence of Heavy Metals  
Absence of Halogenated Flame Retardants  
  
Ortho-Phthalates  
FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)  
EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
FloorScore® Certified

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

 <div>Rejuvenate 73100 LRV 73.1   L* 88.49 Weldrod 05201</div>	 <div>Inspire 73104 Weldrod 05202</div>	 <div>Delight 73110 Weldrod 05206</div>	 <div>Radiate 73112 Weldrod 05207</div>	 <div>Uplift 73120 Weldrod 05226</div>	 <div>Heal 73144 Weldrod 05237</div>
 <div>Warmth 73155 Weldrod 05209</div>	 <div>Zest 73201 Weldrod 05241</div>	 <div>Flourish 73325 Weldrod 05242</div>	 <div>Nourish 73370 Weldrod 05245</div>	 <div>Benefit 73415 Weldrod 05232</div>	 <div>Soothe 73447 Weldrod 05239</div>
 <div>Exhilarate 73485 Weldrod 05240</div>	 <div>Elevate 73505 Weldrod 05205</div>	 <div>Excite 73515 Weldrod 05203</div>	 <div>Restore 73518 Weldrod 05204</div>	 <div>Strength 73530 Weldrod 05225</div>	 <div>Invigorate 73535 Weldrod 05238</div>
 <div>Energy 73675 Weldrod 05219</div>	 <div>Thrive 73700 Weldrod 05243</div>	 <div>Abundance 73740 Weldrod 05230</div>	 <div>Comfort 73755 Weldrod 05228</div>	 <div>Balance 73761 Weldrod 05244</div>	 <div>Robust 73855 Weldrod 05220</div>

