

Vitality Sheet

Collection	Vitality	
Style Number	0873V	
Welding Rod Style Number	353VS	
Construction	Commercial Homogeneous Sheet	
Class / ASTM F1913		
Finish	ExoGuard®	
	U.S.	Metric
Overall Thickness	0.079 in	2 mm
Installation Type	Dry Back	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.58 ft w x 65.94 ft l	2.01 m w x 20.10 m l
Area per Roll	47.84 sy/roll	40 sq m/roll
Weight per Roll	284 lbs	128.82 kg



Recommended Installation Method



Reverse

Coordinating Products

Sheet: Vitality Tones, Vitality Hues

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *2000 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Coefficient of Friction (ASTM D2047, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited Warranty](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency

Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure

FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

6.91 Kg CO₂/M²

Low Embodied Carbon

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 3rd Party Certified

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions

Part 1: (C): Restrict Asbestos Precondition

X08 Hazardous Material Reduction

Part 1: Limit Hazardous Materials Optimization

X10 Volatile Compound Reduction

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

X10 Volatile Compound Reduction

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

X11 Long Term Emissions Control

Part 2: Flooring Optimization

Absence of Asbestos**Absence of Heavy Metals****Absence of Halogenated Flame Retardants****Ortho-Phthalates****FloorScore Certificate**

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization

Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials

Option 1: Product Category Calculations

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**FloorScore Certified**
[Installation Guidelines](#)
[Maintenance Guidelines](#)
Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Rejuvenate 73100 LRV 73.1 L* 88.49 Weldrod 05201	Inspire 73104 Weldrod 05202	Delight 73110 Weldrod 05206	Radiate 73112 Weldrod 05207	Uplift 73120 Weldrod 05226	Heal 73144 Weldrod 05237
					
Warmth 73155 Weldrod 05209	Zest 73201 Weldrod 05241	Flourish 73325 Weldrod 05242	Nourish 73370 Weldrod 05245	Benefit 73415 Weldrod 05232	Soothe 73447 Weldrod 05239
					
Exhilarate 73485 Weldrod 05240	Elevate 73505 Weldrod 05205	Excite 73515 Weldrod 05203	Restore 73518 Weldrod 05204	Strength 73530 Weldrod 05225	Invigorate 73535 Weldrod 05238
					
Energy 73675 Weldrod 05219	Thrive 73700 Weldrod 05243	Abundance 73740 Weldrod 05230	Comfort 73755 Weldrod 05228	Balance 73761 Weldrod 05244	Robust 73855 Weldrod 05220

