

Vitality Sheet

Colección	Vitality	
Número De Estilo	0873V	
Número De Estilo De Barra De Soldadura	353VS	
Construcción clase	Manta Vinílica Comercial Homogénea	
Terminación	ExoGuard®	
	U.s.	Metric
Espesor Total Del Producto	0.079 in	2 mm
Installation Type	Dry Back	
Adhesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Tamaño Real Del Rollo	6.58 ft w x 65.94 ft l	2.01 m w x 20.10 m l
Área Por Rollo	47.84 sy/roll	40 sq m/roll
Peso Por Rollo	284 lbs	128.82 kg



Método De Instalación Recomendado



Inverso

Productos Que Combinan

Sheet: Vitality Tones, Vitality Hues

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

## Diversity &amp; Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

## Atributos + Certificaciones

## Health &amp; Wellbeing

Material Ingredient Transparency

Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure

FloorScore® | Certificado

## Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

Embodied Carbon (Cradle to Gate)

Total Recycled Content

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, &amp; ISO 21930:2017

6.91 Kg CO<sub>2</sub>/M<sup>2</sup>

Low Embodied Carbon

6.91 Kg CO<sub>2</sub>/M<sup>2</sup>

0% (Pre-Consumer 0% | Post-Consumer 0%)

## Global Product Assessment

CE Marking (EN 14041) | Certificado Tercerizado

Country of Origin | Imported

## WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition

X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt

X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt

X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

**Absence of Asbestos****Absence of Heavy Metals****Absence of Halogenated Flame Retardants****Ortho-Phthalates****FloorScore Certificate**

## Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción  
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)

Crédito EQ: Materiales de baja emisión

Opción 1: Cálculos de categoría de producto

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017****FloorScore® Certified**

## Installation Guidelines

## Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways

					
Rejuvenate 73100 LRV 73.1   L* 88.49 Weldrod 05201	Inspire 73104 Weldrod 05202	Delight 73110 Weldrod 05206	Radiate 73112 Weldrod 05207	Uplift 73120 Weldrod 05226	Heal 73144 Weldrod 05237
					
Warmth 73155 Weldrod 05209	Zest 73201 Weldrod 05241	Flourish 73325 Weldrod 05242	Nourish 73370 Weldrod 05245	Benefit 73415 Weldrod 05232	Soothe 73447 Weldrod 05239
					
Exhilarate 73485 Weldrod 05240	Elevate 73505 Weldrod 05205	Excite 73515 Weldrod 05203	Restore 73518 Weldrod 05204	Strength 73530 Weldrod 05225	Invigorate 73535 Weldrod 05238
					
Energy 73675 Weldrod 05219	Thrive 73700 Weldrod 05243	Abundance 73740 Weldrod 05230	Comfort 73755 Weldrod 05228	Balance 73761 Weldrod 05244	Robust 73855 Weldrod 05220

