

Vitality Sheet


수집	Vitality	
스타일 번호	0873V	
응접봉 스타일 번호	353VS	
수업		
끝	ExoGuard®	
	미국	미터법
전체 제품 두께	0.079 in	2 mm
Installation Type	Dry Back	
권장 접착제	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

포장

실제 롤 크기	6.58 ft w x 65.94 ft l	2.01 m w x 20.10 m l
롤당 면적	47.84 sy/roll	40 sq m/roll
롤 당 무게	284 lbs	128.82 kg



권장 설치 방법



공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
내열성 (ASTM F1514)	Passes
내광성 (ASTM F1515)	Passes
화학 물질에 대한 내성 (ASTM F925)	Passes
복사 패널 (ASTM E648)	Passes, Class I
마찰 계수 (ASTM D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

[Commercial 15 Year Underbed Bond Warranty](#)  
[15년 상용 제한](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)  
Embodied Carbon (Cradle to Gate)  
Life-Cycle Carbon Emissions  
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득  
6.91 Kg Co<sub>2</sub>/M<sup>2</sup>  
Low Embodied Carbon  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 타사 인증 획득  
Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt  
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt  
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

**Absence of Asbestos**  
**Absence of Heavy Metals**  
**Absence of Halogenated Flame Retardants**  
  
**Ortho-Phthalates**  
**FloorScore Certificate**

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축  
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)  
EQ 크레딧 : 저 발광 재료  
옵션 1 : 제품 범주 계산

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore® Certified**

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways

					
Rejuvenate 73100 LRV 73.1   L* 88.49 Weldrod 05201	Inspire 73104 Weldrod 05202	Delight 73110 Weldrod 05206	Radiate 73112 Weldrod 05207	Uplift 73120 Weldrod 05226	Heal 73144 Weldrod 05237
					
Warmth 73155 Weldrod 05209	Zest 73201 Weldrod 05241	Flourish 73325 Weldrod 05242	Nourish 73370 Weldrod 05245	Benefit 73415 Weldrod 05232	Soothe 73447 Weldrod 05239
					
Exhilarate 73485 Weldrod 05240	Elevate 73505 Weldrod 05205	Excite 73515 Weldrod 05203	Restore 73518 Weldrod 05204	Strength 73530 Weldrod 05225	Invigorate 73535 Weldrod 05238
					
Energy 73675 Weldrod 05219	Thrive 73700 Weldrod 05243	Abundance 73740 Weldrod 05230	Comfort 73755 Weldrod 05228	Balance 73761 Weldrod 05244	Robust 73855 Weldrod 05220

