

Vitality Sheet

コレクション	Vitality	
スタイルナンバー	0873V	
溶接棒スタイル番号	353VS	
クラス		
仕上げ	ExoGuard®	
	米国	メートル法
製品全体の厚さ	0.079 in	2 mm
Installation Type	Dry Back	
推奨接着剤	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	6.58 ft w x 65.94 ft l	2.01 m w x 20.10 m l
ロールあたりの面積	47.84 sy/roll	40 sq m/roll
ロールごとの重量	284 lbs	128.82 kg



推奨インストール方法



パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
柔軟性 (astm F137)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
摩擦係数(astm D2407、滑り抵抗)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

属性+認定

Climate Impact

Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Embodied Carbon (Cradle to Gate)	6.91 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)

Global Product Assessment

FloorScore® | 認証取得
CE Marking (EN 14041) | 第三者認証取得
Country of Origin | Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築
環境製品宣言-オプション1：環境製品宣言 (EPD)
EQクレジット：低排出材料
オプション1：製品カテゴリの計算

[Installation Guidelines](#)
[Maintenance Guidelines](#)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified





Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Rejuvenate 73100 LRV 73.1 Weldrod 05201	Inspire 73104 Weldrod 05202	Delight 73110 Weldrod 05206	Radiate 73112 Weldrod 05207	Uplift 73120 Weldrod 05226	Heal 73144 Weldrod 05237
					
Warmth 73155 Weldrod 05209	Zest 73201 Weldrod 05241	Flourish 73325 Weldrod 05242	Nourish 73370 Weldrod 05245	Benefit 73415 Weldrod 05232	Soothe 73447 Weldrod 05239

					
Exhilarate 73485 Weldrod 05240	Elevate 73505 Weldrod 05205	Excite 73515 Weldrod 05203	Restore 73518 Weldrod 05204	Strength 73530 Weldrod 05225	Invigorate 73535 Weldrod 05238
					
Energy 73675 Weldrod 05219	Thrive 73700 Weldrod 05243	Abundance 73740 Weldrod 05230	Comfort 73755 Weldrod 05228	Balance 73761 Weldrod 05244	Robust 73855 Weldrod 05220

