

Innate


コレクション	Innate + In Tandem	
スタイルナンバー	0895V	
建設	市販のバイオベースのポリウレタン異種タイル	
クラス	ASTM F06 (In Development)	
仕上げ	ExoGuard+®	
	米国	メートル法
公称寸法	13 in w x 26 in l	33 cm w x 67 cm l
実際の寸法	13.18 in w x 26.38 in l	33.48 cm w x 67.01 cm l
製品全体の厚さ	0.098 in	2.5 mm
エッジプロファイル	スクエア エッジ	
Installation Type	Dry Back	
インストール	Direct Glue	
推奨接着剤	4200 Resilient Tile 4 Gallon	

包装

ボックスあたりの個数	16 pcs	
ボックスあたりの面積	38.64 sq ft	3.59 sq m
ボックスあたりの重量	28 lbs	12.7 kg



推奨インストール方法



コーディネート商品

PVC-Free: In Tandem Sheet, In Tandem

パフォーマンス + テスト

静荷重 (astm F970)	Passes (Modified), *1500 lbs	このテストは、さまざまなスタイルと構造の相対的な特性を比較することを目的としています。結果は実験室でのテストに基づいており、比較の目的で使用されています。実際の負荷制限は異なる場合があります。
残留圧痕 (astm F1914)	Passes	
耐熱性 (astm F1514)	Passes	
耐光性 (astm F1515)	Passes	
耐薬品性 (astm F925)	Passes	
放射パネル (astm E648)	Passes, Class I	
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証
Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

属性+認定

Health & Wellbeing

- Material Ingredient Transparency
- Greenhealth Approved | Yes
Cradle to Cradle Certified™ | シルバーレベル (バージョン 3.1)
Health Product Declaration (HPD) | 1000 ppm Disclosure
Declare | LBC 準拠
- Indoor Air Quality
- FloorScore® | 認証取得

Climate Impact

- Environmental Product Declaration (EPD)
- EN 15804 および ISO 14025 に基づく 第三者認証取得
- Embodied Carbon (Cradle to Gate)
- 4.31 Kg CO₂/M²
- Life-Cycle Carbon Emissions
- Carbon Neutral
- Total Recycled Content
- 0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

- CE Marking (EN 14041) | 第三者認証取得
- Country of Origin | Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート	Health Product Declaration (HPD) 100 Ppm Disclosure
MRクレジット：製品の開示と最適化の構築 材料成分-オプション2：材料成分の最適化	C2C Silver Level (Version 3.1)
MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	3rd Party Certified in Accordance with EN 15804, ISO 14025
MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials - Option 2: Leadership Extraction Practices	Bio-Based Materials - Meets Astm D6866 And ISO 16620-2
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore Certified

追加情報

**Meets or exceeds all local and national regulations in country of manufacture.

Installation Guidelines


Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply
and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of
this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse
suppliers from which to choose. Compared to non-allowable spend which includes
categories in which we do not have domestic, small or diverse suppliers available to
meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

