

In Tandem Sheet

|                          |  |        |
|--------------------------|--|--------|
| Collection               | Innate + In Tandem   |        |
| Style Number             | 0897V  |        |
| Welding Rod Style Number | 270VS  |        |
| Construction             | Comm Bio-Based Polyurethane Het Sheet W/Fibreglass               |        |
| Class / ASTM F1303       | ASTM F06 (In Development)  |        |
| Finish                   | ExoGuard+®   |        |
|                          | U.s.   | Metric |
| Overall Thickness        | 0.098 in   | 2.5 mm |
| Installation Type        | Dry Back   |        |
| Installation             | Direct Glue  |        |
| Recommended Adhesive     | 4200 Resilient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon |        |

Packaging

|                  |                        |                      |
|------------------|------------------------|----------------------|
| Actual Roll Size | 6.59 ft w x 65.62 ft l | 2.01 m w x 20.00 m l |
| Area Per Roll    | 48.08 sy/roll          | 40.2 sq m/roll       |
| Weight Per Roll  | 321.88 lbs             | 146 kg               |



Recommended Installation Method



Non Reverse

Coordinating Products

PVC-Free: Innate, In Tandem, Innate Sheet

Performance + Testing

|   |   |  |
|---|---|--|
| Static Load (ASTM F970)                               | Passes (Modified), *1500 lbs  | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| Residual Indentation (ASTM F1914)                     | Passes  |  |
| Flexibility (ASTM F137)                               | Passes  |  |
| Resistance to Heat (ASTM F1514)                       | Passes  |  |
| Resistance to Light (ASTM F1515)                      | Passes  |  |
| Resistance to Chemicals (ASTM F925)                   | Passes  |  |
| Radiant Panel (ASTM E648)                             | Passes, Class I   |  |
| coefficient of friction (ASTM D2407, slip resistance) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |  |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Material Health & Environmental Certifications

|   |   |
|---|---|
| Health & Wellbeing                      |   |
| Material Ingredient Transparency        | Cradle to Cradle Certified™   Silver Level (Version 3.1)<br>Health Product Declaration (HPD)   1000 ppm Disclosure<br>Declare   LBC Compliant |
| Indoor Air Quality                      | FloorScore®   Certified   |
| Climate Impact                          |   |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with EN 15804, ISO 14025  |
| Embodied Carbon (Cradle to Gate)        | 2.76 Kg Co <sub>2</sub> /M <sup>2</sup>   |
| Life-Cycle Carbon Emissions             | Carbon Neutral  |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)   |
| Global Product Assessment               |   |
|   | CE Marking (EN 14041)   3rd Party Certified<br>Country of Origin   Imported   |

WELL V2 Contribution Credit

|  |   |
|--|---|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition                         | C2C Silver Level (Version 3.1)            |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt                   | C2C Silver Level (Version 3.1)            |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | C2C Silver Level (Version 3.1)            |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt                               | C2C Silver Level (Version 3.1)            |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt                                     | FloorScore® & Greenguard Gold Certificate |
| X13 Enhanced Material Precaution Part 1: Select Optimized Materials Optimization – max 2 pts             | C2C Silver Level (Version 3.1)            |
| X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization – max 2 pts                 | C2C Silver Level (Version 3.1)            |

## Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 2: Material Ingredient Optimization

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

MR Credit: Building Product Disclosure and Optimization  
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

[Installation Guidelines](#)

**Health Product Declaration (HPD) | 100 Ppm Disclosure**

**C2C Silver Level (Version 3.1)**

**3rd Party Certified in Accordance with EN 15804, ISO 14025**

**Bio-Based Materials - Meets Astm D6866 And ISO 16620-2**


**FloorScore® Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


## Available Colorways




Buff 97105  
V2 - Slight Variation  
Weldrod 00105




Pane 97130  
V1 - Uniform Appearance  
Weldrod 00130



Spry 97250  
V2 - Slight Variation  
Weldrod 00250




Bough 97510  
V2 - Slight Variation  
Weldrod 00510




Winnow 97560  
V2 - Slight Variation  
Weldrod 00560




Link 97580  
V1 - Uniform Appearance  
Weldrod 00580




Groove 97590  
V2 - Slight Variation  
Weldrod 00590



Laurel 97600  
V2 - Slight Variation  
Weldrod 00600




Twain 97650  
V2 - Slight Variation  
Weldrod 00650



Raffia 97710  
V2 - Slight Variation  
Weldrod 00710



Burl 97760  
V2 - Slight Variation  
Weldrod 00760



Linden 97790  
V1 - Uniform Appearance  
Weldrod 00790

## Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

