

In Tandem Sheet

Collection	Innate + In Tandem	
Style Number	0897V	
Welding Rod Style Number	270VS	
Construction	Comm Bio-Based Polyurethane Het Sheet W/Fiberglass	
Class / ASTM F1303	ASTM F06 (In Development)	
Finish	ExoGuard+®	
	U.S.	Metric
Overall Thickness	0.098 in	2.5 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	4200 Resilient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	
Packaging		
Actual Roll Size	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
Area per Roll	48.08 sy/roll	40.2 sq m/roll
Weight per Roll	321.88 lbs	146 kg



Recommended Installation Method



Non-Reverse

Coordinating Products

PVC-Free: Innate, In Tandem, Innate Sheet, Innate Linen Sheet, Innate Stria Tile

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Coefficient of Friction (ASTM D2047, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- [15 Year Commercial Limited Warranty](#)
- [Commercial 15 Year Underbed Bond Warranty](#)

Material Health & Environmental Certifications

Health & Wellbeing

- Material Ingredient Transparency
- Cradle to Cradle Certified™ | Silver Level (Version 3.1)  
Health Product Declaration (HPD) | 1000 ppm Disclosure  
Declare | LBC Compliant
- Indoor Air Quality
- FloorScore® | Certified

Climate Impact

- Environmental Product Declaration (EPD)
- 3rd Party Certified in Accordance with EN 15804, ISO 14025
- Embodied Carbon (Cradle to Gate)
- 4.31 Kg Co<sub>2</sub>/M<sup>2</sup>
- Life-Cycle Carbon Emissions
- Carbon Neutral
- Total Recycled Content
- 0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

- GSA | Approved
- CE Marking (EN 14041) | 3rd Party Certified
- Country of Origin | Imported

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions  
Part 1: (C): Restrict Asbestos Precondition
- C2C V3.1 Silver Certification
- X08 Hazardous Material Reduction  
Part 1: Limit Hazardous Materials Optimization
- C2C V3.1 Silver Certification
- X10 Volatile Compound Reduction  
Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization
- C2C V3.1 Silver Certification
- X10 Volatile Compound Reduction  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization
- C2C V3.1 Silver Certification
- X11 Long Term Emissions Control  
Part 2: Flooring Optimization
- FloorScore & Greenguard Gold Certificate
- X13 Enhanced Material Precaution  
Part 1: Select Optimized Materials Optimization
- C2C V3.1 Silver Certification
- X14 Material Transparency  
Part 1: Promote Ingredient Disclosure Optimization
- C2C V3.1 Silver Certification

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 2: Material Ingredient Optimization

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

MR Credit: Building Product Disclosure and Optimization  
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

[Installation Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure

C2C V3.1 Silver Certification

3rd Party Certified in Accordance with EN 15804, ISO 14025

Bio-Based Materials - Meets Astm D6866 And ISO 16620-2


FloorScore Certified

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

