

In Tandem Sheet

コレクション	Innate + In Tandem	
スタイルナンバー	0897V	
溶接棒スタイル番号	270VS	
建設	グラスファイバーを使用した市販のバイオベースのポリウレタン異種シート	
クラス	ASTM F06 (In Development)	
仕上げ	ExoGuard+®	
	米国	メートル法
製品全体の厚さ	0.098 in	2.5 mm
Installation Type	Dry Back	
インストール	Direct Glue	
推奨接着剤	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
ロールあたりの面積	48.08 sy/roll	40.2 sq m/roll
ロールごとの重量	321.88 lbs	146 kg



推奨インストール方法



Non Reverse

コーディネート商品

PVC-Free: Innate, In Tandem

パフォーマンス + テスト

静荷重 (astm F970)	Passes (Modified), *1500 lbs
残留圧痕 (astm F1914)	Passes
柔軟性 (astm F137)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
放射パネル (astm E648)	Passes, Class I
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

このテストは、さまざまなスタイルと構造の相対的な特性を比較することを目的としています。結果は実験室でのテストに基づいており、比較の目的で使用されています。実際の負荷制限は異なる場合があります。

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

Commercial 15 Year Underbed Bond Warranty

属性+認定

Health & Wellbeing	
Material Ingredient Transparency	Cradle to Cradle Certified™ シルバーレベル (バージョン 3.1) Health Product Declaration (HPD) 1000 ppm Disclosure Declare LBC 準拠
Indoor Air Quality	FloorScore® 認証取得
Climate Impact	
Environmental Product Declaration (EPD)	EN 15804 および ISO 14025 に基づく 第三者認証取得
Embodied Carbon (Cradle to Gate)	4.31 Kg Co ₂ /M ²
Life-Cycle Carbon Emissions	Carbon Neutral
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 第三者認証取得 Country of Origin Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート	Health Product Declaration (HPD) 100 Ppm Disclosure
MRクレジット：製品の開示と最適化の構築 材料成分-オプション2：材料成分の最適化	C2C V3.1 Silver Certification
MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	3rd Party Certified in Accordance with EN 15804, ISO 14025
MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials - Option 2: Leadership Extraction Practices	Bio-Based Materials - Meets Astm D6866 And ISO 16620-2
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore Certified

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply
and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of
this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

