

In Tandem Sheet

수집	Innate + In Tandem	
스타일 번호	0897V	
용접봉 스타일 번호	270VS	
구성	섬유 유리를 가진 상업적인 생물 근거한 폴리 우레탄 이중 장	
수업	ASTM F06 (In Development)	
끝	ExoGuard+®	
	미국	미터법
전체 제품 두께	0.098 in	2.5 mm
Installation Type	Dry Back	
설치	Direct Glue	
권장 접착제	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

포장

실제 롤 크기	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
롤당 면적	48.08 sy/roll	40.2 sq m/roll
롤 당 무게	321.88 lbs	146 kg



권장 설치 방법



Non Reverse

코디네이팅 제품

PVC-Free: Innate, In Tandem

공연 + 테스트

- 정적 하중 (Astm F970)
- 잔차 들어 쓰기 (Astm F1914)
- 유연성 (Astm F137)
- 내열성 (Astm F1514)
- 내광성 (Astm F1515)
- 화학 물질에 대한 내성 (Astm F925)
- 복사 패널 (Astm E648)
- 마찰 계수 (astm D2407, 미끄러짐 저항)

- Passes (Modified), *1500 lbs
- Passes
- Passes
- Passes
- Passes
- Passes
- Passes, Class I

≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

이 테스트는 다양한 스타일과 구성의 상대적인 속성을 비교하기 위한 것입니다. 결과는 실험실 테스트를 기반으로 하며 비교 목적으로 사용됩니다. 실제 하중 한계는 다를 수 있습니다.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

15년 상용 제한

Commercial 15 Year Underbed Bond Warranty

속성 + 인증

Health & Wellbeing	
Material Ingredient Transparency	Cradle to Cradle Certified™ Silver 레벨(버전 3.1) Health Product Declaration (HPD) 1000 ppm Disclosure Declare LBC 규격
Indoor Air Quality	FloorScore® 인증
Climate Impact	
Environmental Product Declaration (EPD)	EN 15804, ISO 14025에 따라 타사 인증 획득
Embodied Carbon (Cradle to Gate)	4.31 Kg Co ₂ /M ²
Life-Cycle Carbon Emissions	Carbon Neutral
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 타사 인증 획득 Country of Origin Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축 재료 성분-옵션 1 : 재료 성분보고	Health Product Declaration (HPD) 100 Ppm Disclosure
MR 크레딧 : 제품 공개 및 최적화 구축 재료 성분-옵션 2 : 재료 성분 최적화	C2C V3.1 Silver Certification
MR 크레딧 : 제품 공개 및 최적화 구축 환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)	3rd Party Certified in Accordance with EN 15804, ISO 14025
MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials - Option 2: Leadership Extraction Practices	Bio-Based Materials - Meets Astm D6866 And ISO 16620-2
EQ 크레딧트 : 저 발광 재료 옵션 1 : 제품 범주 계산	FloorScore Certified

Installation Guidelines









Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

