

In Tandem Sheet

Coleção	Innate + In Tandem	
Número Do Produto	0897V	
Número Do Estilo Da Haste De Soldagem	270VS	
Construção	Manta Comercial Bio-Based De Poliuretano (Het Sheet) Com Fibra De Vidro	
classe	ASTM F06 (In Development)	
Acabamento	ExoGuard+®	
	U.s.	Metric
Espessura Total Do Produto	0.098 in	2.5 mm
Installation Type	Dry Back	
Instalação	Direct Glue	
Adesivo Recomendado	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Empacotamento

Tamanho Real Do Rolo	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
Área Por Rolo	48.08 sy/roll	40.2 sq m/roll
Peso Por Rolo	321.88 lbs	146 kg



Método De Instalação Recomendado



Non Reverse

Produtos Coordenados

PVC-Free: Innate, In Tandem, Innate Sheet, Innate Linen Sheet, Innate Stria Tile

Desempenho + Teste

Carga Estática (Astm F970)	Passes (Modified), *1500 lbs	Este Teste Tem Como Objetivo Comparar Propriedades Relativas De Diferentes Estilos E Construções. Os Resultados São Baseados Em Um Teste De Laboratório E Usados Para Fins Comparativos - O Limite De Carga Na Vida Real Pode Variar.
Recuo Residual (Astm F1914)	Passes	
Flexibilidade (Astm F137)	Passes	
Resistência Ao Calor (Astm F1514)	Passes	
Resistência À Luz (Astm F1515)	Passes	
Resistência A Produtos Químicos (Astm F925)	Passes	
Painel Radiante (Astm E648)	Passes, Class I	
Coefficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Cradle to Cradle Certified™ Nível Prata (Versão 3.1) Health Product Declaration (HPD) 1000 ppm Disclosure Declare Compatível LBC
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com with EN 15804, ISO 14025
Embodied Carbon (Cradle to Gate)	4.31 Kg Co ₂ /M ²
Life-Cycle Carbon Emissions	Carbon Neutral
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado 3rd Party Country of Origin Imported

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	Health Product Declaration (HPD) 100 Ppm Disclosure
MR Credit: Divulgação e otimização de produtos de construção Ingredientes do material - Opção 2: Otimização do ingrediente do material	C2C V3.1 Silver Certification
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	3rd Party Certified in Accordance with EN 15804, ISO 14025
MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials - Option 2: Leadership Extraction Practices	Bio-Based Materials - Meets Astm D6866 And ISO 16620-2
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	FloorScore Certified

[Installation Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

