

## In Tandem Sheet


Collection	<b>Innate + In Tandem</b>	
Style Number	<b>0897V</b>	
Welding Rod Style Number	<b>270VS</b>	
Construction	<b>Comm Bio-Based Polyurethane Het Sheet W/Fiberglass</b>	
Class / ASTM F1303	<b>ASTM F06 (In Development)</b>	
Finish	<b>ExoGuard+®</b>	
	U.S.	Metric
Overall Thickness	<b>0.098 in</b>	<b>2.5 mm</b>
Installation Type	<b>Dry Back</b>	
Installation	<b>Direct Glue</b>	
Recommended Adhesive	<b>4200 Resilient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon</b>	

### Packaging

Actual Roll Size	<b>6.59 ft w x 65.62 ft l</b>	<b>2.01 m w x 20.00 m l</b>
Area per Roll	<b>48.08 sq ft/roll</b>	<b>40.2 sq m/roll</b>
Weight per Roll	<b>321.88 lbs</b>	<b>146 kg</b>



### Recommended Installation Method



Non-Reverse

### Coordinating Products

None: Innate, In Tandem, Innate Sheet, Innate Linen Sheet, Innate Stria Tile

### Performance + Testing

Static Load (ASTM F970)	<b>Passes (Modified), *1500 lbs</b>	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	<b>Passes</b>	
Flexibility (ASTM F137)	<b>Passes</b>	
Resistance to Heat (ASTM F1514)	<b>Passes</b>	
Resistance to Light (ASTM F1515)	<b>Passes</b>	
Resistance to Chemicals (ASTM F925)	<b>Passes</b>	
Radiant Panel (ASTM E648)	<b>Passes, Class I</b>	
Coefficient of Friction (ASTM D2047, Slip Resistance)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

[15 Year Commercial Limited Warranty](#)

[Commercial 15 Year Underbed Bond Warranty](#)

## Material Health & Environmental Certifications

### Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Silver Level (Version 3.1)  
Health Product Declaration (HPD) | 1000 ppm Disclosure  
Declare | LBC Compliant

### Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with EN 15804, ISO 14025

Embodied Carbon (Cradle to Gate)

4.31 Kg Co<sub>2</sub>/M<sup>2</sup>

Life-Cycle Carbon Emissions

Carbon Neutral

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

### Global Product Assessment

FloorScore® | Certified

GSA | Approved

CE Marking (EN 14041) | 3rd Party Certified

Greenguard (Certification, Gold, Private Label) | Certified

Country of Origin | Imported

## WELL V2 Contribution Credit

X01 Fundamental Material Precautions

Part 1: (C): Restrict Asbestos Precondition

**C2C V3.1 Silver Certification**

X08 Hazardous Material Reduction

Part 1: Limit Hazardous Materials Optimization

**C2C V3.1 Silver Certification**

X10 Volatile Compound Reduction

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

**C2C V3.1 Silver Certification**

X10 Volatile Compound Reduction

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

**C2C V3.1 Silver Certification**

X11 Long Term Emissions Control

Part 2: Flooring Optimization

**FloorScore & Greenguard Gold Certificate**

X13 Enhanced Material Precaution

Part 1: Select Optimized Materials Optimization

**C2C V3.1 Silver Certification**

X14 Material Transparency

Part 1: Promote Ingredient Disclosure Optimization

**C2C V3.1 Silver Certification**

## Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 2: Material Ingredient Optimization

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

MR Credit: Building Product Disclosure and Optimization  
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

### Installation Guidelines

**Health Product Declaration (HPD) | 100 Ppm Disclosure**

**C2C V3.1 Silver Certification**

**3rd Party Certified in Accordance with EN 15804, ISO 14025**

**Bio-Based Materials - Meets Astm D6866 And ISO 16620-2**

**FloorScore & Greenguard Gold Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways



### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

