

In Tandem Sheet

Collection	Innate + In Tandem	
Numéro De Style	0897V	
Référence De La Baguette De Soudure	270VS	
Construction	Rouleauhet Commerciale EN Polyuréthane Biosourcé Avec Fibre De Verre	
classe	ASTM F06 (In Development)	
Finition	ExoGuard+®	
	Impérial	Métrique
Épaisseur Générale Du Produit	0.098 in	2.5 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Emballage

Dimensions Réelles Du Rouleau	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
Surface Par Rouleau	48.08 sy/roll	40.2 sq m/roll
Poids Par Rouleau	321.88 lbs	146 kg



Méthodes d'Installation Conseillées



Non Reverse

Coordination Des Produits

None: Innate, In Tandem, Innate Sheet, Innate Linen Sheet, Innate Stria Tile

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Souplesse (Astm F137)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Niveau Argent (Version 3.1)
Health Product Declaration (HPD) | 1000 ppm Disclosure
Declare | Conforme LBC

Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes EN 15804, ISO 14025

Embodied Carbon (Cradle to Gate)

4.31 Kg CO₂/M²

Life-Cycle Carbon Emissions

Carbon Neutral

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé
CE Marking (EN 14041) | Certifié Par Un Tiers
Greenguard (Certification, Gold, Private Label) | Agréé
Country of Origin | Imported

Contribution Au Certificat Vert Leed

- « Crédit MR : Divulgation et optimisation des produits de construction
- « Crédit MR : Divulgation et optimisation des produits de construction
- « Crédit MR : Divulgation et optimisation des produits de construction

MR Credit: Building Product Disclosure and Optimization
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices
Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure
C2C V3.1 Silver Certification
3rd Party Certified in Accordance with EN 15804, ISO 14025
Bio-Based Materials - Meets Astm D6866 And ISO 16620-2
FloorScore & Greenguard Gold Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

