

In Tandem Sheet

コレクション	Innate + In Tandem	
スタイルナンバー	0897V	
溶接棒スタイル番号	270VS	
建設	グラスファイバーを使用した市販のバイオベースのポリウレタン異種シート	
クラス	ASTM F06 (In Development)	
仕上げ	ExoGuard+®	
	米国	メートル法
製品全体の厚さ	0.098 in	2.5 mm
Installation Type	Dry Back	
インストール	Direct Glue	
推奨接着剤	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
ロールあたりの面積	48.08 sy/roll	40.2 sq m/roll
ロールごとの重量	321.88 lbs	146 kg



推奨インストール方法



Non Reverse

コーディネート商品

None: Innate, In Tandem

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
柔軟性 (astm F137)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証  
[Commercial 15 Year Underbed Bond Warranty](#)

属性+認定

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | シルバーレベル (バージョン 3.1)  
Health Product Declaration (HPD) | 1000 ppm Disclosure  
Declare | LBC 準拠

Climate Impact

Environmental Product Declaration (EPD)  
Embodied Carbon (Cradle to Gate)  
Life-Cycle Carbon Emissions  
Total Recycled Content

EN 15804 および ISO 14025 に基づく第三者認証取得  
4.31 Kg Co<sub>2</sub>/M<sup>2</sup>  
Carbon Neutral  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | 認証取得  
CE Marking (EN 14041) | 第三者認証取得  
Greenguard (Certification, Gold, Private Label) | 認証取得  
Country of Origin | Imported

グリーンリード貢献クレジット











MRクレジット：製品の開示と最適化の構築  
材料成分-オプション1：材料成分レポート  
MRクレジット：製品の開示と最適化の構築  
材料成分-オプション2：材料成分の最適化  
MRクレジット：製品の開示と最適化の構築  
環境製品宣言-オプション1：環境製品宣言 (EPD)  
MR Credit: Building Product Disclosure and Optimization  
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices  
EQクレジット：低排出材料  
オプション1：製品カテゴリの計算

Health Product Declaration (HPD) | 100 Ppm Disclosure  
  
C2C V3.1 Silver Certification  
  
3rd Party Certified in Accordance with EN 15804, ISO 14025  
  
Bio-Based Materials - Meets Astm D6866 And ISO 16620-2  
  
FloorScore & Greenguard Gold Certified

[Installation Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

