

In Tandem Sheet

수집	Innate + In Tandem	
스타일 번호	0897V	
용접봉 스타일 번호	270VS	
구성	섬유 유리를 가진 상업적인 생물 근거한 폴리 우레탄 이중 장	
수업	ASTM F06 (In Development)	
끝	ExoGuard+®	
	미국	미터법
전체 제품 두께	0.098 in	2.5 mm
Installation Type	Dry Back	
설치	Direct Glue	
권장 접착제	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

포장

실제 롤 크기	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
롤당 면적	48.08 sy/roll	40.2 sq m/roll
롤 당 무게	321.88 lbs	146 kg



권장 설치 방법



Non Reverse

코디네이팅 제품

None: Innate, In Tandem

공연 + 테스트

잔차 들어 쓰기 (Astm F1914)	Passes
유연성 (Astm F137)	Passes
내열성 (Astm F1514)	Passes
내광성 (Astm F1515)	Passes
화학 물질에 대한 내성 (Astm F925)	Passes
마찰 계수(asm D2407, 미끄러짐 저항)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

15년 상용 제한  
[Commercial 15 Year Underbed Bond Warranty](#)

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Silver 레벨(버전 3.1)  
Health Product Declaration (HPD) | 1000 ppm Disclosure  
Declare | LBC 규격

Climate Impact

Environmental Product Declaration (EPD)  
Embodied Carbon (Cradle to Gate)  
Life-Cycle Carbon Emissions  
Total Recycled Content

EN 15804, ISO 14025에 따라 타사 인증 획득  
4.31 Kg Co<sub>2</sub>/M<sup>2</sup>  
Carbon Neutral  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | 인증  
CE Marking (EN 14041) | 타사 인증 획득  
Greenguard (Certification, Gold, Private Label) | 인증  
Country of Origin | Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축  
재료 성분-옵션 1 : 재료 성분보고  
MR 크레딧 : 제품 공개 및 최적화 구축  
재료 성분-옵션 2 : 재료 성분 최적화  
MR 크레딧 : 제품 공개 및 최적화 구축  
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)  
MR Credit: Building Product Disclosure and Optimization  
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices  
EQ 크레딧 : 저 발광 재료  
옵션 1 : 제품 범주 계산  
[Installation Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure  
  
C2C V3.1 Silver Certification  
  
3rd Party Certified in Accordance with EN 15804, ISO 14025  
  
Bio-Based Materials - Meets Astm D6866 And ISO 16620-2  
  
FloorScore & Greenguard Gold Certified

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Buff 97105 V2 - Slight Variation Weldrod 07105	Pane 97130 V1 - Uniform Appearance Weldrod 07130	Spry 97250 V2 - Slight Variation Weldrod 07250	Bough 97510 V2 - Slight Variation Weldrod 07510	Winnow 97560 V2 - Slight Variation Weldrod 07560	Link 97580 V1 - Uniform Appearance Weldrod 07580
					
Groove 97590 V2 - Slight Variation Weldrod 07590	Laurel 97600 V2 - Slight Variation Weldrod 07600	Twain 97650 V2 - Slight Variation Weldrod 07650	Raffia 97710 V2 - Slight Variation Weldrod 07710	Burl 97760 V2 - Slight Variation Weldrod 07760	Linden 97790 V1 - Uniform Appearance Weldrod 07790

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

