

Inspire

コレクション	Mindful Play	
スタイルナンバー	0884V	
建設	Heavy Commercial Luxury Vinyl Tile	
クラス	Class III, Type B	
仕上げ	ExoGuard+®	
	米国	メートル法
公称寸法	12 in w x 24 in l	30 cm w x 61 cm l
実際の寸法	12.00 in w x 24.00 in l	30.48 cm w x 60.96 cm l
摩耗層の厚さ	20 mil (0.02 in)	0.51 mm
製品全体の厚さ	0.098 in	2.5 mm
エッジプロファイル	スクエア エッジ	
Installation Type	Dry Back	
インストール	Direct Glue	
推奨接着剤	S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

ボックスあたりの個数	18 pcs	
ボックスあたりの面積	36 sq ft	3.34 sq m
ボックスあたりの重量	32.4 lbs	14.7 kg



推奨インストール方法



コーディネート商品

Carpet Tile: Think Tile, Engage Tile, Impact Tile

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
放射パネル (astm E648)	Passes, Class I
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

[15年の商用限定保証](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

属性+認定

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

[Health Product Declaration \(HPD\) | 1000 ppm Disclosure](#)  
[FloorScore® | 認証取得](#)

Climate Impact

Environmental Product Declaration (EPD)  
  
Total Recycled Content

[ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得](#)  
  
30% (Pre-Consumer 30% | Post-Consumer 0%)

Global Product Assessment

[Re\[tum\] Reclamation Program\\* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Shaw Manufactured Resilient Within The United States And Canada At No Cost to The Customer.](#)  
  
[CE Marking \(EN 14041\) | 第三者認証取得](#)  
[Country of Origin | United States](#)

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築  
材料成分-オプション1：材料成分レポート  
MRクレジット：製品の開示と最適化の構築  
環境製品宣言-オプション1：環境製品宣言 (EPD)  
EQクレジット：低排出材料  
オプション1：製品カテゴリーの計算

[Health Product Declaration \(HPD\) | 100 Ppm Disclosure](#)  
  
[3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017](#)  
  
[FloorScore Certified](#)

追加情報

\* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](#).













[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](#) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply  
and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of  
this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse  
suppliers from which to choose. Compared to non-allowable spend which includes  
categories in which we do not have domestic, small or diverse suppliers available to  
meet our needs.

Visit [shawcontract.com/testing](#) for more information.

Available Colorways

 <div>Clarity 84111 LRV 25.2   L* 57.27 V4 - Substantial Variation</div>	 <div>Lime 84325 LRV 34.9   L* 65.68 V4 - Substantial Variation</div>	 <div>Teal 84405 LRV 9.1   L* 36.14 V4 - Substantial Variation</div>	 <div>Blue 84429 LRV 8.1   L* 34.22 V4 - Substantial Variation</div>	 <div>Escape 84505 LRV 6.9   L* 31.63 V4 - Substantial Variation</div>	 <div>Nuance 84515 LRV 24.4   L* 56.52 V4 - Substantial Variation</div>
 <div>Encourage 84535 LRV 24.2   L* 56.33 V4 - Substantial Variation</div>	 <div>Transform 84585 LRV 13.6   L* 43.68 V4 - Substantial Variation</div>	 <div>Experience 84595 LRV 11   L* 39.6 V4 - Substantial Variation</div>	 <div>Orange 84668 LRV 14.3   L* 44.65 V4 - Substantial Variation</div>	 <div>Achieve 84760 LRV 9.9   L* 37.71 V4 - Substantial Variation</div>	 <div>Purple 84965 LRV 6.9   L* 31.61 V4 - Substantial Variation</div>

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

