

Vertical Edge Tile

|                             |             |   |
|-----------------------------|-------------|---|
| Stijlnummer                 | 59114       |   |
| Collectie                   | On The Edge |   |
| Producttype                 | Tapijttegel |   |
| Construction                | Standard    | Data + Performance                        |
| Type Fabricage              | ISO 2424    | tufted 1/12"   47.2 per 10cm              |
| Uitzicht                    | ISO 2424    | Multilevel-Patroonlus                     |
| Verfmethode                 | EN 994      | 100% In Oplossing Geverfd                 |
| Productformaat              | EN 994      | 46 cm x 91 cm   18 in x 36 in             |
| Vezel                       | ISO 2424    | Ecosolution Q® Polyamide 6                |
| Totale Dikte                | ISO 1765    | 6.0 mm                                    |
| Afgewerkte Pooldikte        | ISO 1766    | 3.2 mm                                    |
| Totale Massa                | ISO 8543    | 2981 g/m²                                 |
| Getuft Gewicht              | ISO 2424    | 746 g/m²                                  |
| Effectieve Poolmassa        | ISO 8543    | 457 g/m²                                  |
| Pooldichtheid               | ISO 8543    | 0.146 g/cm³                               |
| Totaal Gerecycleerde Inhoud |             | 61% (pre-consumer 61%   post-consumer 0%) |




Gegevens

|                                  |               |                               |
|----------------------------------|---------------|-------------------------------|
| Steken                           | ISO 1763      | 203,000/m²   43 per 10cm      |
| Beschermende Behandelingen       |               | SSP® Shaw Grondbescherming    |
| Elektrostatische Weerstand       | ISO 6356      | ≤ 2.0 kv (Stroll Test)        |
| Gebruik Classificatie            | EN 1307       | 33 Commercial Heavy           |
| Luxeklasse                       | EN 1307       | LC2                           |
| Dimensionale Stabiliteit         | EN 986        | ≤ 0.2%                        |
| Contactgeluidsisolatie           | ISO 10140     | 22 Db (Predicted)             |
| Geluidsabsorptieclassificatie    | ISO 354/11654 | 0.15 Aw   Class E (Predicted) |
| Warmteweerstand m² K/w           | ISO 8302      | 0.065 M² K/W Tog 0.65         |
| Weerstand Tegen Droog Uitglijden | ISO 13893     | Pass/No Pulled Loops          |
| Kleurvastheid Voor Licht         | ISO 105-B02   | >6                            |
| Ontvlambaarheid                  | EN 13501-1    | Bfl-S1 (Adhered Testing)      |
| Stoel Met Wieltjes               | EN 985        | ≥2.4 Continuous Use           |

Levenslang Commercieel Beperkt subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Aanbevolen Installatiemethode



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

Coördinerende Producten

Carpet Tile: **Minimal Tile, Merge Tile**

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

|   |   |
|---|---|
| Declaration of Performance              | <b>EU.DOP/2895/CPR/1016/1017/T</b>  |
| Cradle to Cradle gecertificeerd™        | <b>Silver Level (Version 4.0)</b>   |
| Health Product Declaration (HPD)        | <b>1,000 ppm (Parts Per Million) Disclosure</b>   |
| Environmental Product Declaration (EPD) | <b>3de Partij Gecertificeerd in Overeenstemming Met ISO14044, ISO14025 &amp; EN15804</b>  |
| Living Building Challenge (LBC)         | <b>Vrij Van Chemische Producten Die Op De Rode Lijst Staan</b>  |
| Verklaar                                | <b>Voldoet Aan LBC</b>  |
| nsf 140                                 | <b>Goud</b>   |
| Building Research Establishment (BRE)   | <b>A+ Health/A+ Retail 0.372/0.498 Ecopoints</b>  |
| Singapore Green Label                   | <b>Gecertificeerd</b>   |
| milieugarantie                          | <b>Re[turn] Reclamation Program*   Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.</b> |
| productverpakking                       | <b>100% Recycleerbaar</b>   |
| land van herkomst                       | <b>Verenigde Staten</b>   |
| BREEAM Contribution Credit              | <b>Certificate of Approval<br/>Schools/Offices/Health/Industrial Shed<br/>Retail</b>  |

Well V2 Contribution Credit

|  |  |
|--|--|
| X08 Hazardous Material Reduction<br>Part 1: Limit Hazardous Materials Optimization                   | <b>C2C Silver Level (Version 4.0)</b>          |
| X10 Volatile Compound Reduction<br>Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization | <b>C2C Silver Level (Version 4.0)</b>          |
| X11 Long Term Emissions Control<br>Part 2: Flooring Optimization                                     | <b>Green Label Plus Certification: GLP5563</b> |
| X13 Enhanced Material Precaution<br>Part 1: Select Optimized Materials Optimization                  | <b>C2C Silver Level (Version 4.0)</b>          |
| X14 Material Transparency<br>Part 1: Promote Ingredient Disclosure Optimization                      | <b>C2C Silver Level (Version 4.0)</b>          |















Groen Leed Bijdragekrediet

|   |  |
|---|--|
| "MR-krediet: openbaarmaking en optimalisering van bouwproducten<br>Milieuproductverklaringen - Optie 1: Milieuproductverklaring (EPD)"        | <b>3rd Party Certified in Accordance with ISO14044, ISO14025 &amp; EN15804</b>   |
| "MR-krediet: Openbaarmaking en optimalisering van bouwproducten<br>Materiaalingrediënten - Optie 1: Rapportage materiaalingrediënten"         | <b>HPD (Version 2.1) or C2C Silver Level (Version 4.0)</b>   |
| "MR-krediet: openbaarmaking en optimalisering van bouwproducten<br>Materiaalingrediënten - Optie 2: Optimalisering van materiaalingrediënten" | <b>C2C Silver Level (Version 4.0)</b>  |
| MR Credit: Building Product Disclosure and Optimization<br>Sourcing of Raw Materials - Option 2: Leadership Extraction Practices              | <b>Environmental Guarantee: Re[turn] Reclamation Program*   Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.</b> |
| "EQ-krediet: materialen met lage emissie Optie 1: Berekeningen per productcategorie"  | <b>Green Label Plus Certification: GLP5563</b>   |
| MR Credit: Interiors Life-Cycle Impact Reduction<br>Option 3: Design for Flexibility  | <b>Ecoworx Tile with Lokdots Installation System</b>   |

Memberships

|                                 |                                 |
|---------------------------------|---------------------------------|
| WGBC Framework                  | WGBC Framework                  |
| UKGBC                           | UKGBC                           |
| Emirates Green Building Council | Emirates Green Building Council |
| Chemsec                         | Chemsec                         |

Lichtreflectiewaarde

|   |   |  |  |   |   |
|---|---|--|--|---|---|
| <br>Oatmeal Margin 67155<br>LRV 17    | <br>Paprika Margin 67156<br>LRV 15.1 | <br>Dolphin Brink 67505<br>LRV 4.6  | <br>Navy Brink 67506<br>LRV 2.5      | <br>Pewter Limit 67515<br>LRV 20.6 | <br>Blue Limit 67516<br>LRV 20.7     |
| <br>Gunmetal Verge 67555<br>LRV 10    | <br>Ochre Verge 67556<br>LRV 13.8    | <br>Shimmer Fringe 67585<br>LRV 6.4 | <br>Brite Green Fri 67586<br>LRV 6.9 | <br>Mineralite Boun 67752<br>LRV 7 | <br>Sundried Bounda 67753<br>LRV 6.1 |
| <br>Sterling Seam 67761<br>LRV 12.6 | <br>Eggplant Seam 67762<br>LRV 8.5 |  |  |   |   |

Aanvullende Informatie

|   |  |
|---|--|
| <p>* To learn more about the recyclability of our products and our re[TURN], please visit <a href="https://shawcontract.com/sustainability">shawcontract.com/sustainability</a>.</p> <p>**Meets or exceeds all local and national regulations in country of manufacture.</p> <p>***This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.</p> <p><a href="#">Installation Guidelines</a></p> <p><a href="#">Maintenance Guidelines</a></p> <p><a href="#">levenslang commercieel beperkt</a></p> | <p>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.</p> <p>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.</p> <p>Visit <a href="https://shawcontract.com/testing">shawcontract.com/testing</a> for more information.</p> |
|---|--|

