


Ornate Tile

|                       |   |
|-----------------------|---|
| Product Type          | Carpet Tile   |
| Collection            | Modern Edit   |
| Style Number          | 5T166   |
| Construction          | Multi-Level Pattern/Cut Loop  |
| Fiber                 | Ecosolution Q100™ Nylon   |
| Primary Backing       | Synthetic   |
| Secondary Backing     | Ecoworx® Tile   |
| Protective Treatments | SSP® Shaw Soil Protection   |
| Recommended Adhesive  | LokDots, 3000 Carpet Tile 1 Gallon, 4151 Multi-Use Carpet Tile 4 Gallon, 5000 Carpet Tile 1 Gallon, LokWorx Adhesive Tabs, 3800 Indoor Outdoor Carpet Tile 4 Gallon, 5000 Carpet Tile 4 Gallon or 3000 Carpet Tile 4 Gallon |

|                         |               |                |
|-------------------------|---------------|----------------|
|                         | u.s.          | metric         |
| Product Size            | 18 in x 36 in | 46 cm x 91 cm  |
| Area Per Carton         | 45 ft²        | 4.18 m²        |
| Pieces Per Carton       | 10 pcs        |                |
| Gauge                   | 1/12 in       | 47.2 per 10 cm |
| Stitches                | 9.5 per in    | 38.0 per 10 cm |
| Finished Pile Thickness | 0.127 in      | 3.23 mm        |
| Average Density         | 9638 oz/yd³   | 0.357 g/cm³    |
| Kilotex                 |               | 20.85          |
| Total Thickness         | 0.334 in      | 8.48 mm        |
| Tufted Weight           | 34 oz/yd²     | 1152.8 g/m²    |



Recommended Installation Method



Data + Testing

|                            |  |
|----------------------------|--|
| Radiant Panel              | Class I  |
| Nbs Smoke                  | Less Than 450  |
| Electrostatic Propensity   | Less Than 3.5 kv   |
| Cri Green Label Plus (Glp) | GLP5563  |
| Pill Test                  | Pass*  |
| Ada Compliance             | >0.6, Meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes*** |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Lifetime Commercial Limited

Coordinating Products

LVT: **Intricate**  
Carpet Tile: **Rethread Tile**  
Broadloom: **Edition, Inherit**

Material Health & Environmental Certifications

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Health & Wellbeing

Material Ingredient Transparency

**Cradle to Cradle Certified® | Silver Level (Version 4.0)**  
**Health Product Declaration (HPD) | 1,000 ppm Disclosure**  
**Living Building Challenge (LBC) | Free of Red List Chemicals**  
**Declare | LBC Compliant**  
**NSF 140 | Gold**  
**CRI Green Label Plus (GLP) | GLP5563**

Indoor Air Quality

Climate Impact

Environmental Product Declaration (EPD)  
Embodied Carbon (Cradle to Gate)  
Life-Cycle Carbon Emissions  
Total Recycled Content  
Product Packaging

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**  
**4.03 kg CO<sub>2</sub>/m<sup>2</sup>**  
**Carbon Neutral**  
**63% (Pre-Consumer 63% | Post-Consumer 0%)**  
**100% Recyclable**

Global Product Assessment



















**Singapore Green Label | Certified**  
**CE Marking (EN 14041) | 3rd Party Certified**  
**Environmental Guarantee\* | Re[turn] Reclamation Program\* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.**  
**Country of Origin\*\* | USA**

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)  
MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting  
MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 2: Material Ingredient Optimization  
MR Credit: Building Product Disclosure and Optimization  
Sourcing of Raw Materials - Option 2: Leadership Extraction Practices  
EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations  
MR Credit: Interiors Life-Cycle Impact Reduction  
Option 3: Design for Flexibility

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**  
**HPD (Version 2.1) or C2C Silver Level (Version 4.0)**  
**C2C Silver Level (Version 4.0)**  
**Environmental Guarantee: Re[turn] Reclamation Program\* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.**  
**Green Label Plus Certification: GLP5563**  
**Ecoworx Tile with Lokdots Installation System**

## Available Colorways

|   |  |  |   |  |  |
|---|--|--|---|--|--|
|   |   |   |   |   |   |
| Ivory 64144<br>LRV 20.6   L* 52.56  | Apricot Ivory 64145<br>LRV 19.8   L* 51.59   | Ochre 64155<br>LRV 14.6   L* 45.05   | Heritage Blue 64481<br>LRV 4.4   L* 24.91   | Indigo 64496<br>LRV 2.9   L* 19.45   | Antique 64504<br>LRV 13.1   L* 42.88   |
|   |   |   |   |   |   |
| Eternal 64505<br>LRV 2.5   L* 17.82   | Eternal Cobalt 64506<br>LRV 2.3   L* 17.1  | Glass 64515<br>LRV 22.6   L* 54.66   | Green Glass 64516<br>LRV 20.3   L* 52.2   | Grey Slate 64535<br>LRV 15.3   L* 46.01  | Yellow Slate 64536<br>LRV 13.5   L* 43.5   |
|  |  |  |  |  |  |
| Vintage Grey 64595<br>LRV 5.8   L* 29   | Vintage Teal 64596<br>LRV 4.7   L* 25.8  | Hearth 64760<br>LRV 5.9   L* 29.2  | Coral Hearth 64761<br>LRV 4.9   L* 26.35  | Umber 64855<br>LRV 4.7   L* 25.98  | Brocade 64911<br>LRV 4.5   L* 25.23  |

## Additional Information

\* To learn more about the recyclability of our products and our re[TURN], please visit [shawcontract.com/sustainability](https://shawcontract.com/sustainability).

\*\*Meets or exceeds all local and national regulations in country of manufacture.

\*\*\*This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
November 24, 2024

3 of 3