


## Bon Jour II Tile

Collection	<b>Steppin Out</b>
Numéro Du Style	<b>5T032</b>
Construction	<b>Côte De Liaison à L'aiguille</b>
Fibre	<b>Polyester Pet</b>
Méthode De Coloration	<b>100% Solution Teinte</b>
Sous-couche Primaire	<b>Polypropylène</b>
Sous-couche Secondaire	<b>Dalle Ecoworx®</b>
Traitements Protecteurs	<b>Résistance Aux Taches Inhérente</b>
Adhésif Recommandé	<b>LokDots, 3000 Carpet Tile 1 Gallon, 4151 Multi-Use Carpet Tile 4 Gallon, 5000 Carpet Tile 1 Gallon, LokWorx Adhesive Tabs, 3800 Indoor Outdoor Carpet Tile 4 Gallon, 5000 Carpet Tile 4 Gallon or 3000 Carpet Tile 4 Gallon</b>



	u.s.	metric
Dimensions Du Produit	<b>24 in x 24 in</b>	<b>61 cm x 61 cm</b>
Surface Par Carton	<b>48 ft²</b>	<b>4.46 m²</b>
Pièces Par Carton	<b>12 pcs</b>	
Points	<b>0.0 per in</b>	<b>0.5 per 10 cm</b>
Densité Moyenne	<b>5284 per cu. yd.</b>	<b>0.196 g/cm³</b>
Epaisseur Du Velours	<b>0.451 in</b>	<b>11.46 mm</b>
Poids Tufté	<b>50.5 oz/yd²</b>	<b>1,712.24 g/m²</b>

## Méthodes d'Installation Conseillées



### Quarter Turn

## Données + Tests Et Essai

Test d'Inflammabilité	<b>Pass</b>
Panneau Rayonnant (Astm E648)	<b>Class I</b>
Nbs Smoke	<b>Less Than 450</b>
Propension Électrostatique	<b>Less Than 3.5 kv</b>
Label Cri Green Label Plus (Glp)	<b>GLP0520</b>
Ada Compliance	<b>&gt;0.6, Meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes***</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Garanties

### Durée De Vie Commerciale Limitée

Coordination Des Produits

Carpet Tile: **Welcome II Tile, Entrée Tile**

Broadloom: **Welcome II, Bon Jour II**


Attributs + Certifications

Certification Cradle to Cradle™ (C2C)	<b>Bronze Level (Version 3.1)</b>
Déclaration sanitaire de produit (HPD)	<b>Transparence 1 000 ppm</b>
Déclaration environnementale de produit (EPD)	<b>Certifié Par Un Organisme Tiers Conformément Aux Normes ISO14044, ISO 14025 &amp; EN15804</b>
Living Building Challenge (LBC)	<b>Free of Red List Chemicals</b>
Déclarer	<b>LBC Compliant</b>
NSF 140	<b>or</b>
CRI Green Label Plus (GLP)	<b>GLP0520</b>
Singapore Green Label	<b>Certifié</b>
garantie environnementale	<b>Re[turn] Reclamation Program*   Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.</b>
emballage du produit	<b>100% Recyclable</b>
pays d'origine	<b>USA</b>

Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO14044, ISO14025 &amp; EN15804</b>
MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 1: Material Ingredient Reporting	<b>HPD (Version 2.1) or C2C Silver Level (Version 3.1)</b>
MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 2: Material Ingredient Optimization	<b>C2C Bronze Level (Version 3.1)</b>
MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials - Option 2: Leadership Extraction Practices	<b>Environmental Guarantee: Re[turn] Reclamation Program*   Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.</b>
"Crédit EQ : matériaux faibles émissions Option 1 : calculs par catégorie de produit"	<b>Certified</b>
MR Credit: Interiors Life-Cycle Impact Reduction Option 3: Design for Flexibility	<b>Ecoworx Tile with Lokdots Installation System</b>

### Available Colorways



### Informations Supplémentaires

\* To learn more about the recyclability of our products and our re[TURN], please visit [shawcontract.com/sustainability](https://shawcontract.com/sustainability).

\*\*Meets or exceeds all local and national regulations in country of manufacture.

\*\*\*This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.



**PVC-Free**

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
May 14, 2024

3 of 3