

Dye Lab Tile

Numéro Du Style	5T041	
Collection	Dye Lab	
Type De Produit	Dalles De Moquette	
Construction	Standard	Data + Performance
Type De Fabrication	ISO 2424	tufted 1/10" 39.4 per 10cm
Construction	ISO 2424	Pile Coupée
Dimensions Du Produit	EN 994	61 cm x 61 cm 24 in x 24 in
Fibre	ISO 2424	Ecosolution Q® Polyamide 6
Epaisseur Du Velours	ISO 1765	8.1 mm
Épaisseur Du Velours Fini	ISO 1766	5.2 mm
Poids Total	ISO 8543	3483 g/m²
Poids Tufté	ISO 2424	1221 g/m²
Poids Du Velours Utile	ISO 8543	840 g/m²
Densité Du Velours	ISO 8543	0.162 g/cm³
Contenu Recyclé Total	64% (pre-consumer 64% post-consumer 0%)	





Données


Points	ISO 1763	169,000/m² 43 per 10cm
Traitements Protecteurs	SSP® Shaw Protection Du Sol	
Propension Electrostatique	ISO 6356	≤ 2.0 kv (Stroll Test)
Classification d'Utilisation	EN 1307	33 Commercial Heavy
Classification Luxe	EN 1307	LC4
Stabilité Dimensionnelle	EN 986	≤ 0.2%
Isolation Acoustique	ISO 10140	27 Db
Classification d'Absorption Sonore	ISO 354/11654	0.20 Aw Class E
Résistance Thermique m² K/w	ISO 8302	0.090 M² K/W Tog 0.90
Dry Slip Resistance	ISO 13893	Pass/No Pulled Loops
Résistance De La Couleur À La Lumière	ISO 105-B02	>6
Inflammabilité	EN 13501-1	Cfl-S1 (Adhered Testing)
Chaise À Roulette	EN 985	≥2.4 Continuous USE


Durée De Vie Commerciale Limitée subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Méthodes d'Installation Conseillées


Monolithic


Quarter Turn


Brick


Ashlar


33


33


33



33


27 dB



27 dB


27 dB



27 dB



13


EU.DOP/2895/CPR/1013/0116/T
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905
BL NETHERLANDS (NLD)
Notified Body 2895



22

UK.DOP/0338/CPR/1013/0116/T
SHAW EUROPE LIMITED BLACKADDIE RD,
SANQUHAR DG4 6DB, UNITED KINGDOM
Approved Body 0338


E1
HCHO


Cfl-s1


Lightning bolt


DS

EN14041:2004/AC:2006

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

Attributs + Certifications

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Declaration of Performance	EU.DOP/2895/CPR/1013/0116/T
Certification Cradle to Cradle™ (C2C)	Silver Level (Version 4.0)
Déclaration sanitaire de produit (HPD)	1,000 ppm (Parts Per Million) Disclosure
Déclaration environnementale de produit (EPD)	Certifié Par Un Organisme Tiers Conformément Aux Normes ISO 14044, ISO 14025 & EN15804
Living Building Challenge (LBC)	Free of Red List Chemicals
Déclarer	LBC Compliant
NSF 140	or
Building Research Establishment (BRE)	A Offices/A+ Retail 0.433/0.583 Ecopoints
Singapore Green Label	Certifié
garantie environnementale	Re[turn] Reclamation Program* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet.
emballage du produit	100% Recyclable
pays d'origine	USA
BREEAM Contribution Credit	Certificate of Approval Schools/Offices/Health/Industrial Shed Retail

Well V2 Contribution Credit

X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	C2C Silver Level (Version 4.0)
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	C2C Silver Level (Version 4.0)
X11 Long Term Emissions Control Part 2: Flooring Optimization	Green Label Plus Certification: GLP5563
X13 Enhanced Material Precaution Part 1: Select Optimized Materials Optimization	C2C Silver Level (Version 4.0)
X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization	C2C Silver Level (Version 4.0)






















Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 1: Material Ingredient Reporting	HPD (Version 2.1) or C2C Silver Level (Version 4.0)
MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 2: Material Ingredient Optimization	C2C Silver Level (Version 4.0)
MR Credit: Building Product Disclosure and Optimization Sourcing of Raw Materials - Option 2: Leadership Extraction Practices	Environmental Guarantee: Re[turn] Reclamation Program* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Ecoworx Carpet. Green Label Plus Certification: GLP5563
"Crédit EQ : matériaux faibles émissions Option 1 : calculs par catégorie de produit"	
MR Credit: Interiors Life-Cycle Impact Reduction Option 3: Design for Flexibility	Ecoworx Tile with Lokdots Installation System

Memberships

WGBC Framework	WGBC Framework
UKGBC	UKGBC
Emirates Green Building Council	Emirates Green Building Council
Chemsec	Chemsec

Indice De Réflexion Lumineuse

					
Osage Orange 41202 LRV 17.2 (range 12.4 - 21.5) L* 48.19 (range 41.91 - 53.48)	→ Fustic Wood 41316 LRV 3 (range 2.8 - 3.2) L* 20.05 (range 19.23 - 20.89)	Fustic Saxon 41396 LRV 8.8 (range 6.6 - 10.4) L* 35.41 (range 30.89 - 38.56)	→ Black Walnut 41402 LRV 12.7 (range 11.6 - 14.6) L* 42.16 (range 40.6 - 45.04)	→ Saxon 41462 LRV 5.7 (range 3.8 - 7.6) L* 28.32 (range 23.11 - 33.17)	→ Cornflower 41480 LRV 4.8 (range 3.1 - 6.3) L* 25.8 (range 20.36 - 30.10)
					
→ Knotweed 41491 LRV 12.0 (range 10.6 - 12.8) L* 41.2 (range 38.9 - 42.43)	→ Indigo 41496 LRV 2.9 (range 2.1 - 3.7) L* 19.6 (range 16.14 - 22.66)	→ Woad 41497 LRV 4.0 (range 2.6 - 5.5) L* 23.4 (range 18.20 - 27.99)	→ Sumac 41504 LRV 9.2 (range 6.4 - 11.8) L* 36.1 (range 30.43 - 40.92)	Logwood 41505 LRV 3.1 (range 2.2 - 4.3) L* 20.4 (range 16.71 - 24.62)	→ Black Tea 41516 LRV 10.1 (range 8.8 - 11.9) L* 38.0 (range 35.55 - 41.09)
					
→ Henna 41535 LRV 12.6 (range 10.7 - 13.8) L* 42.09 (range 39 - 43.97)	→ Iron 41580 LRV 6.8 (range 4.7 - 8.4) L* 31.12 (range 25.83 - 34.8)	Sandalwood 41665 LRV 13.2 (range 11.7 - 15) L* 42.99 (range 40.77 - 45.57)	Lac 41762 LRV 3.5 (range 2.8 - 4.2) L* 21.9 (range 19.27 - 24.34)	Brazil Wood 41855 LRV 2.8 (range 2.1 - 3.3) L* 19.24 (range 16.02 - 21.26)	Madder Root 41864 LRV 7.7 (range 5.1 - 9.3) L* 32.84 (range 26.92 - 36.47)
					
→ Cochineal 41880 LRV 4.9 (range 3.3 - 6.6) L* 26.01 (range 21.03 - 30.80)	→ Beet 41890 LRV 5.3 (range 4.8 - 6) L* 27.43 (range 26.18 - 29.45)	Iris 41965 LRV 3.8 (range 2.7 - 4.8) L* 22.71 (range 18.91 - 26.17)			

Informations Supplémentaires

* To learn more about the recyclability of our products and our re[TURN], please visit shawcontract.com/sustainability.

**Meets or exceeds all local and national regulations in country of manufacture.

***This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[durée de vie commerciale limitée](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.



PVC-Free

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302