

Establish Taskworx® Tile

Stijlnummer	5T331	
Collectie	Assembly	
Producttype	Tapijttegel	
Construction	Standard	Data + Performance
Type Fabricage	ISO 2424	tufted 1/12" 47.2 per 10cm
Uitzicht	ISO 2424	Multilevel-Patroonlus
Verfmethode	EN 994	100% In Oplossing Geveerd
Productformaat	EN 994	25 cm x 100 cm 20 tiles (5 m²) per box
Primaire Backing	ISO 2424	Pet Nonwoven
Secundaire Backing	ISO 2424	Taskworx® Tegel Polymeer Gemodificeerd Bitumen
Vezel	ISO 2424	Ecosolution Q® Polyamide 6
Totale Dikte	ISO 1765	6.0 mm
Afgewerkte Pooldikte	ISO 1766	1.9 mm
Totale Massa	ISO 8543	3881 g/m²
Getuft Gewicht	ISO 2424	653 g/m²
Effectieve Poolmassa	ISO 8543	232 g/m²
Pooldichtheid	ISO 8543	0.125 g/cm³
Totaal Gerecycleerde Inhoud		50% (pre-consumer 50% post-consumer 0%)





Gegevens

Steken	ISO 1763	165,000/m² 35 per 10cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxeklasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	24 Db
Geluidsabsorptieclassificatie	ISO 354/11654	0.15 Aw Class E
Warmteweerstand m² K/w	ISO 8302	0.069 M² K/W Tog 0.69
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wielletjes	EN 985	≥2.4 Continuous USE

15 Jaar Commercieel Beperkt subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

Aanbevolen Installatiemethode



Coördinerende Producten

Carpet Tile: **Establish Comfortworx® Tile, Convene Taskworx® Tile, Support Taskworx® Tile**

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Declaration of Performance	EU.DOP/0493/CPR/0621/0422/BT
Building Research Establishment (BRE)	A+ Health/A+ Retail 0.301/0.399 Ecopoints
land van herkomst	Verenigd Koninkrijk
BREEAM Contribution Credit	Certificate of Approval Schools/Offices/Health/Industrial Shed Retail











Air Quality

Indoor Air Comfort Gold	Certified
M1	Certified

Memberships

WGBC Framework	WGBC Framework
UKGBC	UKGBC
Emirates Green Building Council	Emirates Green Building Council
Chemsec	Chemsec

Lichtreflectiewaarde

					
Brilliant 67325 LRV 17.7 L* 49.07	Vivid 67375 LRV 7.5 L* 33	Clear 67486 LRV 5 L* 26.65	System 67505 LRV 5.5 L* 28.11	Interaction 67515 LRV 18.1 L* 49.57	Network 67535 LRV 14.5 L* 44.98
					
Link 67555 LRV 8.2 L* 34.44	Foundation 67580 LRV 8.2 L* 34.44	Dynamic 67850 LRV 6.1 L* 29.57	Radiant 67855 LRV 8.7 L* 35.44		

Aanvullende Informatie

15 jaar commercieel beperkt	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

