


| | | |
|-----------------------------|------------------|--------------------------------------------------|
| Stijlnummer | 5T334 | |
| Collectie | Simply By Nature | |
| Producttype | Tapijttegel | |
| Construction | Standard | Data + Performance |
| Type Fabricage | ISO 2424 | tufted 1/10" 39.4 per 10cm |
| Uitzicht | ISO 2424 | Multilevel-Patroonlus |
| Verfmethode | EN 994 | 100% In Oplossing Geverfd |
| Productformaat | EN 994 | 50 cm x 50 cm 20 tiles (5 m²) per box |
| Primaire Backing | ISO 2424 | Pet Nonwoven |
| Secundaire Backing | ISO 2424 | Taskworx® Tegel Polymeer Gemodificeerd Bitumen |
| Vezel | ISO 2424 | Ecosolution Q® Polyamide 6 |
| Totale Dikte | ISO 1765 | 6.5 mm |
| Afgewerkte Pooldikte | ISO 1766 | 2.4 mm |
| Totale Massa | ISO 8543 | 4187 g/m² |
| Getuft Gewicht | ISO 2424 | 542 g/m² |
| Effectieve Poolmassa | ISO 8543 | 252 g/m² |
| Pooldichtheid | ISO 8543 | 0.106 g/cm³ |
| Totaal Gerecycleerde Inhoud | | 50% (pre-consumer 50% post-consumer 0%) |

Gegevens

| | | |
|----------------------------------|---------------|----------------------------|
| Steken | ISO 1763 | 160,000/m² 40.7 per 10cm |
| Beschermende Behandelingen | | SSP® Shaw Grondbescherming |
| Elektrostatische Weerstand | ISO 6356 | ≤ 2.0 kv (Stroll Test) |
| Gebruik Classificatie | EN 1307 | 33 Commercial Heavy |
| Luxeklasse | EN 1307 | LC1 |
| Dimensionale Stabiliteit | EN 986 | ≤ 0.2% |
| Contactgeluidsisolatie | ISO 10140 | 27 Db |
| Geluidsabsorptieclassificatie | ISO 354/11654 | 0.20 Aw Class E |
| Warmteweerstand m² K/w | ISO 8302 | 0.076 M² K/W Tog 0.76 |
| Weerstand Tegen Droog Uitglijden | ISO 13893 | Pass / No Pulled Loops |
| Kleurvastheid Voor Licht | ISO 105-B02 | >6 |
| Ontvlambaarheid | EN 13501-1 | Bfl-S1 (Adhered Testing) |
| Stoel Met Wieltjes | EN 985 | ≥2.4 Continuous USE |

15 Jaar Commercieel Beperkt subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Aanbevolen Installatiemethode



27 dB

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302



CE
17

EU.DOP/0493/CPR/0621/0422/BT
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905
BL NETHERLANDS (NLD)
Notified Body 2895

UK
CA
22

UK.DOP/0338/CPR/1220/0422/BT
SHAW EUROPE LIMITED BLACKADDIE RD,
SANQUHAR DG4 6DB, UNITED KINGDOM
Approved Body 0338

E1
HCHO

Bfl-s1

EN14041:2004/AC:2006
For use as an indoor floor covering as specified by the manufacturer

Coördinerende Producten

Carpet Tile: **Arrange Taskworx® Tile, Array Taskworx® Tile, Structure Taskworx® Tile**

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

| | |
|---------------------------------------|--------------------------------------------------------------------------------------|
| Declaration of Performance | EU.DOP/0493/CPR/0621/0422/BT |
| Building Research Establishment (BRE) | A+ Health/A+ Retail 0.301/0.399 Ecopoints |
| land van herkomst | Verenigd Koninkrijk |
| BREEAM Contribution Credit | Certificate of Approval Schools/Offices/Health/Industrial Shed Retail |











Air Quality

| | |
|-------------------------|------------------|
| Indoor Air Comfort Gold | Certified |
| M1 | Certified |

Memberships

| | |
|---------------------------------|----------------------------------------|
| WGBC Framework | WGBC Framework |
| UKGBC | UKGBC |
| Emirates Green Building Council | Emirates Green Building Council |
| Chemsec | Chemsec |

Lichtreflectiewaarde

| | | | | | |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |  |
| Glassy Green 94335 LRV 8 | Shimmery Blue 94485 LRV 7.5 | Chrome Black 94500 LRV 5.2 | Glossy Charcoal 94505 LRV 6.1 | Sterling Silver 94515 LRV 14.1 | Steel Grey 94530 LRV 9.2 |
|  |  |  |  | | |
| Mirror Grey 94535 LRV 16 | Polished Stone 94557 LRV 7.3 | Metallic Beige 94760 LRV 16.9 | Shiny Pebble 94761 LRV 12.1 | | |

Aanvullende Informatie

| | |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 15 jaar commercieel beperkt | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. |
| | This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. |
| | Visit shawcontract.com/testing for more information. |

