



Intent Taskworx® Tile

Stijlnummer	5T336	
Collectie	District	
Producttype	Tapijttegel	
Construction	Standard	Data + Performance
Type Fabricage	ISO 2424	tufted 1/10"   39.4 per 10cm
Uitzicht	ISO 2424	Multilevel-Patroonlus
Verfmethode	EN 994	100% In Oplossing Geverfd
Productformaat	EN 994	50 cm x 50 cm   20 tiles (5 m²) per box
Primaire Backing	ISO 2424	Pet Nonwoven
Secundaire Backing	ISO 2424	Taskworx® Tegel   Polymeer Gemodificeerd Bitumen
Vezel	ISO 2424	Ecosolution Q® Polyamide 6
Totale Dikte	ISO 1765	6.2 mm
Afgewerkte Pooldikte	ISO 1766	2.1 mm
Totale Massa	ISO 8543	4022 g/m²
Getuft Gewicht	ISO 2424	474 g/m²
Effectieve Poolmassa	ISO 8543	219 g/m²
Pooldichtheid	ISO 8543	0.102 g/cm³
Totaal Gerecycleerde Inhoud		51% (pre-consumer 51%   post-consumer 0%)




Gegevens

Steken	ISO 1763	153,000/m²   38.7 per 10cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxeklasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	25db
Geluidsabsorptieclassificatie	ISO 354/11654	0.15 Aw   Class E
Warmteweerstand m² K/w	ISO 8302	0.081 M² K/W Tog 0.81
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wieltjes	EN 985	≥2.4 Continuous USE

15 Jaar Commercieel Beperkt subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Aanbevolen Installatiemethode



EU.DOP/0493/CPR/0621/0422/BT  
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905  
BL NETHERLANDS (NLD)  
Notified Body 2895

UK.DOP/0338/CPR/1220/0422/BT  
SHAW EUROPE LIMITED BLACKADDIE RD,  
SANQUHAR DG4 6DB, UNITED KINGDOM  
Approved Body 0338

EN14041:2004/AC:2006  
For use as an indoor floor covering as specified by the manufacturer

Coördinerende Producten

Carpet Tile: **Purpose Taskworx® Tile, Situation Taskworx® Tile**

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Declaration of Performance	<b>EU.DOP/0493/CPR/0621/0422/BT</b>
Building Research Establishment (BRE)	<b>A+ Health/A+ Retail 0.301/0.399 Ecopoints</b>
land van herkomst	<b>Verenigd Koninkrijk</b>
BREEAM Contribution Credit	<b>Certificate of Approval Schools/Offices/Health/Industrial Shed Retail</b>







Air Quality

Indoor Air Comfort Gold	<b>Certified</b>
M1	<b>Certified</b>

Memberships

WGBC Framework	<b>WGBC Framework</b>
UKGBC	<b>UKGBC</b>
Emirates Green Building Council	<b>Emirates Green Building Council</b>
Chemsec	<b>Chemsec</b>

Lichtreflectiewaarde

					
Stellar 08505 LRV 3.1   L* 20.31	Skylight 08530 LRV 13.4   L* 43.32	Nocturne 08557 LRV 7.7   L* 33.45	Shale 08597 LRV 5.3   L* 27.58	Woodsmoke 08760 LRV 8.9   L* 35.7	Sierra 08761 LRV 11.2   L* 39.87

Aanvullende Informatie

15 jaar commercieel beperkt	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  Visit <a href="https://shawcontract.com/testing">shawcontract.com/testing</a> for more information.
-----------------------------	---

