



Situation Taskworx® Tile

|                             |             |  |
|-----------------------------|-------------|--|
| Stijlnummer                 | 5T338       |  |
| Collectie                   | District    |  |
| Producttype                 | Tapijttegel |  |
| Construction                | Standard    | Data + Performance                               |
| Type Fabricage              | ISO 2424    | tufted 1/10"   39.4 per 10cm                     |
| Uitzicht                    | ISO 2424    | Multilevel-Patroonlus                            |
| Verfmethode                 | EN 994      | 100% In Oplossing Geverfd                        |
| Productformaat              | EN 994      | 50 cm x 50 cm   20 tiles (5 m²) per box          |
| Primaire Backing            | ISO 2424    | Pet Nonwoven                                     |
| Secundaire Backing          | ISO 2424    | Taskworx® Tegel   Polymeer Gemodificeerd Bitumen |
| Vezel                       | ISO 2424    | Ecosolution Q® Polyamide 6                       |
| Totale Dikte                | ISO 1765    | 6.1 mm   |
| Afgewerkte Pooldikte        | ISO 1766    | 2.0 mm   |
| Totale Massa                | ISO 8543    | 3934 g/m²  |
| Getuft Gewicht              | ISO 2424    | 474 g/m²   |
| Effectieve Poolmassa        | ISO 8543    | 210 g/m²   |
| Pooldichtheid               | ISO 8543    | 0.107 g/cm³                                      |
| Totaal Gerecycleerde Inhoud |             | 51% (pre-consumer 51%   post-consumer 0%)        |





Gegevens

|                                  |               |                            |
|----------------------------------|---------------|----------------------------|
| Steken                           | ISO 1763      | 153,000/m²   38.7 per 10cm |
| Elektrostatische Weerstand       | ISO 6356      | ≤ 2.0 kv (Stroll Test)     |
| Gebruik Classificatie            | EN 1307       | 33 Commercial Heavy        |
| Luxeklasse                       | EN 1307       | LC1                        |
| Dimensionale Stabiliteit         | EN 986        | ≤ 0.2%                     |
| Contactgeluidsisolatie           | ISO 10140     | 25db                       |
| Geluidsabsorptieclassificatie    | ISO 354/11654 | 0.15 Aw   Class E          |
| Warmteweerstand m² K/w           | ISO 8302      | 0.081 M² K/W Tog 0.81      |
| Weerstand Tegen Droog Uitglijden | ISO 13893     | Pass / No Pulled Loops     |
| Kleurvastheid Voor Licht         | ISO 105-B02   | >6                         |
| Ontvlambaarheid                  | EN 13501-1    | Bfl-S1 (Adhered Testing)   |
| Stoel Met Wieltjes               | EN 985        | ≥2.4 Continuous USE        |

15 Jaar Commercieel Beperkt subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Aanbevolen Installatiemethode






17

EU.DOP/0493/CPR/0621/0422/BT

OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905  
BL NETHERLANDS (NLD)

Notified Body 2895







22

UK.DOP/0338/CPR/1220/0422/BT

SHAW EUROPE LIMITED BLACKADDIE RD,  
SANQUHAR DG4 6DB, UNITED KINGDOM

Approved Body 0338



EN14041:2004/AC:2006

For use as an indoor floor covering as specified by the manufacturer

Coördinerende Producten

Carpet Tile: **Intent Taskworx® Tile, Purpose Taskworx® Tile**

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

|                                       |  |
|---------------------------------------|--|
| Declaration of Performance            | <b>EU.DOP/0493/CPR/0621/0422/BT</b>  |
| Building Research Establishment (BRE) | <b>A+ Health/A+ Retail 0.301/0.399 Ecopoints</b>                                     |
| land van herkomst                     | <b>Verenigd Koninkrijk</b>   |
| BREEAM Contribution Credit            | <b>Certificate of Approval<br/>Schools/Offices/Health/Industrial Shed<br/>Retail</b> |







Air Quality

|                         |                  |
|-------------------------|------------------|
| Indoor Air Comfort Gold | <b>Certified</b> |
| M1                      | <b>Certified</b> |

Memberships

|                                 |  |
|---------------------------------|--|
| WGBC Framework                  | <b>WGBC Framework</b>                  |
| UKGBC                           | <b>UKGBC</b>                           |
| Emirates Green Building Council | <b>Emirates Green Building Council</b> |
| Chemsec                         | <b>Chemsec</b>                         |

Lichtreflectiewaarde

|  |   |   |  |   |   |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Stellar 08505<br>LRV 3.2   L* 20.71  | Skylight 08530<br>LRV 13.3   L* 43.19   | Nocturne 08557<br>LRV 8.6   L* 35.26  | Shale 08597<br>LRV 5.1   L* 27.11  | Woodsmoke 08760<br>LRV 10.6   L* 38.87  | Sierra 08761<br>LRV 12   L* 41.2  |

Aanvullende Informatie

|                             |   |
|-----------------------------|---|
| 15 jaar commercieel beperkt | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.<br><br>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.<br><br>Visit <a href="https://shawcontract.com/testing">shawcontract.com/testing</a> for more information. |
|-----------------------------|---|

