

Pixel Rectangle Taskworx® Tile

Style Number	5T387	
Collection	Colour Construct	
Product Type	Carpet Tile	
Construction	Standard	Data + Performance
Type of Manufacture	ISO 2424	tufted 1/12" 47.2 per 10cm
Aspect	ISO 2424	Multi-Level Pattern Loop
Dye Method	EN 994	100% Solution Dyed
Dimensions	EN 994	25 cm x 100 cm 20 tiles (5 m²) per box
Primary Backing	ISO 2424	Pet Non-Woven
Secondary Backing	ISO 2424	Taskworx® Tile Polymer Modified Bitumen
Pile Fibre Composition	ISO 2424	Eco Solution Q® Polyamide 6
Total Thickness	ISO 1765	6.3 mm
Effective Pile Thickness	ISO 1766	3.0 mm
Total Mass	ISO 8543	4575 g/m²
Nominal Total Pile Mass	ISO 2424	794 g/m²
Effective Pile Mass	ISO 8543	483 g/m²
Pile Density	ISO 8543	0.161 g/cm³
Total Recycled Content	47% (pre-consumer 47% post-consumer 0%)	



Performance

Number of Tufts	ISO 1763	155,000/m² 32.8 per 10cm
Electrostatic Propensity	ISO 6356	≤ 2.0 kv (Stroll Test)
Use Classification	EN 1307	33 Commercial Heavy
Luxury Class	EN 1307	LC1
Dimensional Stability	EN 986	≤ 0.2%
Impact Sound Insulation	ISO 10140	24 Db
Sound Absorption Classification	ISO 354/11654	0.15 Aw Class E
Thermal Resistance m² K/W	ISO 8302	0.061 M² K/W Tog 0.61
Dry Slip Resistance	ISO 13893	Pass / No Pulled Loops
Colour Fastness To Light	ISO 105-B02	>6
Flammability	EN 13501-1	Bfl-S1 (Adhered Testing)
Castor Chair	EN 985	≥2.4 Continuous Use

15 Year Commercial Limited Warranty subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

Recommended Installation Method



Ashlar



Brick



Herringbone



Stagger



24 dB



17

EU.DOP/0493/CPR/0621/0422/BT
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905
BL NETHERLANDS (NLD)
Notified Body 2895



22

UK.DOP/0338/CPR/1220/0422/BT
SHAW EUROPE LIMITED BLACKADDIE RD,
SANQUHAR DG4 6DB, UNITED KINGDOM
Approved Body 0338



EN14041:2004/AC:2006

For use as an indoor floor covering as specified by the manufacturer

Coordinating Products

Carpet Tile: **Pixel Square Comfortworx® Tile, Pixel Rectangle Comfortworx® Tile, Pixel Hexagon Taskworx® Tile, Pixel Square Taskworx® Tile**

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. TaskWorx® products are Cradle to Cradle Certified® Bronze and assessed for impacts on human health and the environment. This product can be recycled. When it's time to replace, we can collect through our re-[TURN] scheme in EMEA.

Material Health & Environmental Certifications

Certifications below apply exclusively to the carpet tile rug itself and not the LokWorx Tabs adhesive

Declaration of Performance

EU.DOP/0493/CPR/0621/0422/BT

Cradle to Cradle Certified®

Bronze Level (Version 3.1)

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804

Building Research Establishment (BRE)

A+ Health/A+ Retail 0.34/0.453 Ecopoints

Environmental Guarantee*

Take Back Policy Offered For All Taskworx Products

ISO 9001

Certified

Country of Origin**

United Kingdom

BREEAM Contribution Credit

**Certificate of Approval
Schools/Offices/Health/Industrial Shed
Retail**

WELL V2 Contribution Credit

X08 Hazardous Material Reduction

C2C Bronze Level (Version 3.1)

Part 1: Limit Hazardous Materials Optimization

X10 Volatile Compound Reduction

C2C Bronze Level (Version 3.1)

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

X10 Volatile Compound Reduction

C2C Bronze Level (Version 3.1)

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

X11 Long Term Emissions Control

M1> Emissions Class For Building Material

Part 2: Flooring Optimization

X13 Enhanced Material Precaution

C2C Bronze Level (Version 3.1)

Part 1: Select Optimized Materials Optimization

X14 Material Transparency

C2C Bronze Level (Version 3.1)

Part 1: Promote Ingredient Disclosure Optimization

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization

3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804

Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

MR Credit: Building Product Disclosure and Optimization

C2C Bronze Level (Version 3.1)

Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization

C2C Bronze Level (Version 3.1)

Material Ingredients - Option 2: Material Ingredient Optimization

EQ Credit: Low Emitting Materials

Certified

Option 1: Product Category Calculations
















Air Quality

Indoor Air Comfort Gold	Certified
M1	Certified

Memberships

WGBC Framework	WGBC Framework
UKGBC	UKGBC
Emirates Green Building Council	Emirates Green Building Council
Chemsec	Chemsec

Light Reflectance Value

 Yellow 53211 LRV 26.5 L* 58.51	 Chartreuse 53326 LRV 17.3 L* 48.7	 Seaglass 53375 LRV 8.2 L* 34.34	 Aqua 53418 LRV 13.9 L* 44.07	 Wave 53432 LRV 6.8 L* 31.29	 Navy 53485 LRV 5.3 L* 27.47
 Blue 53486 LRV 9.5 L* 36.87	 Arctic 53501 LRV 31 L* 62.47	 Black 53505 LRV 2.6 L* 18.29	 Light Taupe 53506 LRV 16.8 L* 47.96	 Grey 53515 LRV 18.4 L* 49.99	 Beige 53516 LRV 23.4 L* 55.47
 Pewter 53518 LRV 11.3 L* 40.02	 Nickel 53535 LRV 18.9 L* 50.55	 Graphite 53549 LRV 3.9 L* 23.49	 Charcoal 53557 LRV 6.2 L* 29.85	 Steel 53580 LRV 7.5 L* 32.99	 Urban 53592 LRV 11.8 L* 40.83
 Gunmetal 53597 LRV 4.1 L* 23.93	 Orange 53668 LRV 12.8 L* 42.51	 Tangerine 53675 LRV 23.1 L* 55.22	 Taupe 53761 LRV 12.5 L* 42.06	 Poppy 53856 LRV 9.8 L* 37.45	 Magenta 53991 LRV 5.6 L* 28.35

Additional Information

**Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[15 Year Commercial Limited warranty](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company
April 12, 2025

4 of 4