

## Pixel Square Taskworx® Tile

Numéro Du Style	5T386	
Collection	Colour Construct	
Type De Produit	Dalles De Moquette	
Construction	Standard	Data + Performance
Type De Fabrication	ISO 2424	tufted 1/12"   47.2 per 10cm
Construction	ISO 2424	Tufté Structuré Bouclé à Motif
Méthode De Coloration	EN 994	100% Solution Teinte
Dimensions Du Produit	EN 994	50 cm x 50 cm   20 tiles (5 m²) per box
Sous-couche Primaire	ISO 2424	Pet Non-Woven
Sous-couche Secondaire	ISO 2424	Taskworx® Tile   Bitume Modifié Par Polymère
Fibre	ISO 2424	Ecosolution Q® Polyamide 6
Epaisseur Du Velours	ISO 1765	6.3 mm
Épaisseur Du Velours Fini	ISO 1766	3.0 mm
Poids Total	ISO 8543	4575 g/m²
Poids Tufté	ISO 2424	794 g/m²
Poids Du Velours Utile	ISO 8543	483 g/m²
Densité Du Velours	ISO 8543	0.161 g/cm³
Contenu Recyclé Total	49% (pre-consumer 49%   post-consumer 0%)	






### Données


Points	ISO 1763	155,000/m²   32.8 per 10cm
Propension Electrostatique	ISO 6356	≤ 2.0 kv (Stroll Test)
Classification d'Utilisation	EN 1307	33 Commercial Heavy
Classification Luxe	EN 1307	LC1
Stabilité Dimensionnelle	EN 986	≤ 0.2%
Isolation Acoustique	ISO 10140	24 Db
Classification d'Absorption Sonore	ISO 354/11654	0.15 Aw   Class E
Résistance Thermique m² K/w	ISO 8302	0.061 M² K/W Tog 0.61
Dry Slip Resistance	ISO 13893	Pass / No Pulled Loops
Résistance De La Couleur À La Lumière	ISO 105-B02	>6
Inflammabilité	EN 13501-1	Bfl-S1 (Adhered Testing)
Chaise À Roulette	EN 985	≥2.4 Continuous USE





**Limitée Commerciale De 15 Ans** subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

### Méthodes d'Installation Conseillées



  
17  
EU.DOP/0493/CPR/0621/0422/BT  
OOSTERHOUT SHOWROOM, VAARTWEG 10, 4905  
BL NETHERLANDS (NLD)  
Notified Body 2895

  
22  
UK.DOP/0338/CPR/1220/0422/BT  
SHAW EUROPE LIMITED BLACKADDIE RD,  
SANQUHAR DG4 6DB, UNITED KINGDOM  
Approved Body 0338



EN14041:2004/AC:2006  
For use as an indoor floor covering as specified by the manufacturer

## Coordination Des Produits

Carpet Tile: **Pixel Square Comfortworx® Tile, Pixel Rectangle Comfortworx® Tile, Pixel Hexagon Taskworx® Tile, Pixel Rectangle Taskworx® Tile**

## Attributs + Certifications

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Declaration of Performance

Certification Cradle to Cradle™ (C2C)

Déclaration environnementale de produit (EPD)

Building Research Establishment (BRE)

garantie environnementale

ISO 9001

pays d'origine

BREEAM Contribution Credit

**EU.DOP/0493/CPR/0621/0422/BT**

**Bronze Level (Version 3.1)**

**Certifié Par Un Organisme Tiers Conformément Aux Normes ISO 14044, ISO 14025 & EN15804**

**A+ Health/A+ Retail 0.34/0.453 Ecopoints**

**Take Back Policy Offered For All Taskworx Products**

**Certifié**

**United Kingdom**

**Certificate of Approval**

**Schools/Offices/Health/Industrial Shed**

**Retail**

## Well V2 Contribution Credit

X08 Réduction des matières dangereuses Partie 1 : Optimiser la limitation des matières dangereuses – 1 pt

**C2C Bronze Level (Version 3.1)**

X10 Réduction des composés volatils Partie 1 (A) : Optimisation de la gestion des composés organiques volatils (COV) – 1 pt

**C2C Bronze Level (Version 3.1)**

X10 Volatile Compound Reduction

**C2C Bronze Level (Version 3.1)**

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization

X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

**M1> Emissions Class For Building Material**

X13 Précaution accrue à l'égard des matériaux Partie 1 : Choisir des matériaux optimisés – max 2 pts

**C2C Bronze Level (Version 3.1)**

X14 Transparence des matériaux Partie 1 : Promouvoir l'optimisation de la divulgation des composants – max 2 pts

**C2C Bronze Level (Version 3.1)**

## Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**

MR Credit: Building Product Disclosure and Optimisation  
Material Ingredients - Option 1: Material Ingredient Reporting

**C2C Bronze Level (Version 3.1)**

MR Credit: Building Product Disclosure and Optimisation  
Material Ingredients - Option 2: Material Ingredient Optimization

**C2C Bronze Level (Version 3.1)**

"Crédit EQ : matériaux faibles émissions  
Option 1 : calculs par catégorie de produit"

**Certified**

## Air Quality

Indoor Air Comfort Gold

**Certified**

M1

**Certified**

Memberships

- WGBC Framework

UKGBC

Emirates Green Building Council

























Chemsec
- WGBC Framework

UKGBC

Emirates Green Building Council

Chemsec

Indice De Réflexion Lumineuse

					
Yellow 53211 LRV 26.5   L* 58.51	Chartreuse 53326 LRV 17.3   L* 48.7	Seaglass 53375 LRV 8.2   L* 34.34	Aqua 53418 LRV 13.9   L* 44.07	Wave 53432 LRV 6.8   L* 31.29	Navy 53485 LRV 5.3   L* 27.47
					
Blue 53486 LRV 9.5   L* 36.87	Arctic 53501 LRV 31   L* 62.47	Black 53505 LRV 2.6   L* 18.29	Light Taupe 53506 LRV 16.8   L* 47.96	Grey 53515 LRV 18.4   L* 49.99	Beige 53516 LRV 23.4   L* 55.47
					
Pewter 53518 LRV 11.3   L* 40.02	Nickel 53535 LRV 18.9   L* 50.55	Graphite 53549 LRV 3.9   L* 23.49	Charcoal 53557 LRV 6.2   L* 29.85	Steel 53580 LRV 7.5   L* 32.99	Urban 53592 LRV 11.8   L* 40.83
					
Gunmetal 53597 LRV 4.1   L* 23.93	Orange 53668 LRV 12.8   L* 42.51	Tangerine 53675 LRV 23.1   L* 55.22	Taupe 53761 LRV 12.5   L* 42.06	Poppy 53856 LRV 9.8   L* 37.45	Magenta 53991 LRV 5.6   L* 28.35

## Informations Supplémentaires

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[Limitée commerciale de 15 ans](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
June 7, 2025

4 of 4