

Poised Ecoworx S™ Tile


Stijlnummer	5T511	
Collectie	New Path	
Producttype	Tapijttegel	
Construction	Standard	Data + Performance
Type Fabricage	ISO 2424	tufted 1/12"   47.2 per 10cm
Uitzicht	ISO 2424	Multilevel-Patroonlus
Verfmethode	EN 994	100% In Oplossing Geverfd
Productformaat	EN 994	50 cm x 50 cm   20 tiles (5 m²) per box
Primaire Backing	ISO 2424	Pet Nonwoven
Secundaire Backing	ISO 2424	Ecoworx S™ Polyolefin Plastomer
Vezel	ISO 2424	Ecosolution Q100™ Polyamide 6   Bevat 100% Gerecycleerd Materiaal
Totale Dikte	ISO 1765	5.1 mm
Afgewerkte Pooldikte	ISO 1766	1.6 mm
Totale Massa	ISO 8543	2325 g/m²
Getuft Gewicht	ISO 2424	640 g/m²
Effectieve Poolmassa	ISO 8543	229 g/m²
Pooldichtheid	ISO 8543	0.142 g/cm³



Gegevens

Steken	ISO 1763	193,000/m²   41 per 10cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxeklasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	26 Db
Geluidsabsorptieclassificatie	ISO 354/11654	0.20 Aw   Class E
Warmteweerstand m² K/w	ISO 8302	0.062 M² K/W Tog 0.62
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wieltjes	EN 985	≥2.4 Continuous USE

Aanbevolen Installatiemethode



26 dB

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

## Coördinerende Producten

Carpet Tile: **Upbeat Ecoworx S Tile, Positive Ecoworx S Tile**

## Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Cradle to Cradle gecertificeerd™

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

milieugarantie

land van herkomst

BREEAM Contribution Credit

**Zilver Niveau (Versie 3.1)****3de Partij Gecertificeerd in Overeenstemming Met ISO14044, ISO14025 & EN15804****4.14 kg CO<sub>2</sub>/m<sup>2</sup>****Carbon Neutral****Take Back Policy Offered For All Ecoworx S™ Products****Verenigd Koninkrijk****Certificate of Approval****Schools/Offices/Health/Industrial Shed****Retail**

## Well V2 Contribution Credit

X08 Hazardous Material Reduction

Part 1: Limit Hazardous Materials Optimization

**C2C Silver Level (Version 3.1)**

X10 Volatile Compound Reduction

Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization

**C2C Silver Level (Version 3.1)**

X11 Long Term Emissions Control

Part 2: Flooring Optimization

**M1> Emissions Class For Building Material**

X13 Enhanced Material Precaution

Part 1: Select Optimized Materials Optimization

**C2C Silver Level (Version 3.1)**

X14 Material Transparency

Part 1: Promote Ingredient Disclosure Optimization

**C2C Silver Level (Version 3.1)**

## Groen Leed Bijdragekrediet

"MR-krediet: Openbaarmaking en optimalisering van bouwproducten  
Materiaalingrediënten - Optie 1: Rapportage materiaalingrediënten"**C2C Silver Level (Version 3.1)**"MR-krediet: openbaarmaking en optimalisering van bouwproducten  
Materiaalingrediënten - Optie 2: Optimalisering van materiaalingrediënten"**C2C Silver Level (Version 3.1)**

## Air Quality

Indoor Air Comfort Gold

**Certified**

M1

**Certified**

## Memberships

WGBC Framework

**WGBC Framework**

UKGBC

**UKGBC**













Emirates Green Building Council

**Emirates Green Building Council**

Chemsec

**Chemsec**

## Lichtreflectiewaarde

					
Bubbly 10100 LRV 24.7	Warmth 10101 LRV 30.8	Optimistic 10210 LRV 23.1	Considered 10327 LRV 30	Observe 10375 LRV 8.9	Enthusiasm 10411 LRV 26.2
					
Confident 10480 LRV 10.6	Contemplate 10500 LRV 5.2	Satisfied 10515 LRV 15.4	Solace 10580 LRV 11.5	Grateful 10760 LRV 13.2	Cheeky 10870 LRV 9.9

## Aanvullende Informatie

\*\*Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[lifetime commercial limited](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
May 18, 2024

3 of 3