

Stijlnummer	5T585	
Collectie	Floor Architecture III	
Producttype	Tapijttegels	
Construction	Standard	Data + Performance
Type Fabricage	ISO 2424	tufted 1/12" 47.2 per 10cm
Uitzicht	ISO 2424	Multilevel-Patroonlus
Verfmethode	EN 994	100% In Oplossing Geverfd
Productformaat	EN 994	50 cm x 50 cm 20 tiles (5 m²) per box
Primaire Backing	ISO 2424	Pet Nonwoven
Secundaire Backing	ISO 2424	Ecoworx S® Polyolefin Plastomer
Totale Dikte	ISO 1765	5.4 mm
Afgewerkte Pooldikte	ISO 1766	2.1 mm
Totale Massa	ISO 8543	2558 g/m²
Getuft Gewicht	ISO 2424	630 g/m²
Effectieve Poolmassa	ISO 8543	269 g/m²
Pooldichtheid	ISO 8543	0.127 g/cm³
Totaal Gerecycleerde Inhoud		53% (pre-consumer 53% post-consumer 0%)

Steken	ISO 1763	193,000/m² 41 per 10cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxe Klasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	26 Db
Geluidsabsorptieclassificatie	ISO 354/11654	0.20 Aw Class E
Warmteweerstand m² K/w	ISO 8302	0.066 M² K/W Tog 0.66
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wielletjes	EN 985	≥2.4 Continuous USE

The diagram shows five types of brickwork patterns, each represented by a grid of arrows indicating the orientation of the bricks:

- Monolithic:** A 2x2 grid where all arrows point upwards.
- Quarter Turn:** A 2x2 grid where the top row has two upward arrows and the bottom row has two rightward arrows.
- Brick:** A 2x3 grid where the top row has two upward arrows and the bottom row has three upward arrows.
- Ashlar:** A 2x3 grid where the top row has two upward arrows and the bottom row has three upward arrows, with the middle arrow pointing right.
- Random:** A 2x3 grid where the top row has two rightward arrows and the bottom row has three arrows pointing in different directions (right, left, down).



Coördinerende Producten

Carpet Tile: **Stone Comfortworx® Tile, Fragment Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Stone Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Stone Taskworx® Tile, Formation Colours Ecworx S® Tile, Fragment Colours Ecworx S® Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecworx S® Tile, Stone Ecworx S® Tile, Formation Taskworx® Tile, Stone Colours Taskworx® Tile, Stone Colours Ecworx S® Tile**

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Cradle to Cradle gecertificeerd™

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

milieugarantie

land van herkomst

BREEAM Contribution Credit

Zilver Niveau (Versie 3.1)

3de Partij Gecertificeerd in Overeenstemming Met ISO14044, ISO14025 & EN15804

4.21 kg CO₂/m²

Carbon Neutral

Take Back Policy Offered For All Ecworx S® Products

Verenigd Koninkrijk

**Certificate of Approval
Schools/Offices/Health/Industrial Shed
Retail**

Well V2 Contribution Credit

X08 Reductie gevaarlijke stoffen Deel 1: Beperking Optimalisatie Gevaarlijke Materialen - 1 pt **C2C Silver Level (Version 3.1)**

X10 Reductie van vluchtige stoffen Deel 1 (A): Beheer Vluchtige Organische Stoffen (VOS) Optimalisatie - 1 pt **C2C Silver Level (Version 3.1)**

X11 Langetermijn-emissiebeheersing - deel 2: Optimalisering van vloeren - 1 pt **M1> Emissions Class For Building Material**

X13 Verbeterde materiaalvoorzorgsmaatregelen Deel 1: Optimaliseren van materiaalkeuze - max 2 punten **C2C Silver Level (Version 3.1)**

X14 Transparantie van materialen Deel 1: Optimalisatie: Bevorderen van ingrediëntenopenbaarmaking - max 2 punten **C2C Silver Level (Version 3.1)**

Groen Leed Bijdragekrediet

"MR-krediet: Openbaarmaking en optimalisering van bouwproducten Materiaalingrediënten - Optie 1: Rapportage materiaalingrediënten" **C2C Silver Level (Version 3.1)**

"MR-krediet: openbaarmaking en optimalisering van bouwproducten Materiaalingrediënten - Optie 2: Optimalisering van materiaalingrediënten" **C2C Silver Level (Version 3.1)**

Memberships

WGBC Framework

UKGBC

Emirates Green Building Council

Chemsec










WGBC Framework

UKGBC

Emirates Green Building Council

Chemsec

Lichtreflectiewaarde

					
Marble 53100 LRV 27.4 L* 59.35	Azurite 53485 LRV 3.3 L* 21.22	Granite 53500 LRV 3.4 L* 21.73	Mica 53518 LRV 9.4 L* 36.74	Mortar 53530 LRV 13 L* 42.74	Limestone 53535 LRV 13.1 L* 42.86
					
Anthracite 53555 LRV 6.5 L* 30.68	Chromite 53580 LRV 10 L* 37.93	Mix 53597 LRV 7 L* 31.89			

Aanvullende Informatie

**Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[lifetime commercial limited](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company
July 18, 2025

3 of 3