

Stone Colours Ecoworx S® Tile


Style Number	5T587	
Collection	Floor Architecture III	
Product Type	Carpet Tile	
Construction	Standard	Data + Performance
Type of Manufacture	ISO 2424	tufted 1/10" 39.4 per 10cm
Aspect	ISO 2424	Multi-Level Pattern Loop
Dye Method	EN 994	100% Solution Dyed
Dimensions	EN 994	50 cm x 50 cm 20 tiles (5 m²) per box
Primary Backing	ISO 2424	Pet Non-Woven
Secondary Backing	ISO 2424	Ecoworx S® Polyolefin Plastomer
Pile Fibre Composition	ISO 2424	Eco Solution Q100® Polyamide 6 Contains 100% Recycled Content
Total Thickness	ISO 1765	6.1 mm
Effective Pile Thickness	ISO 1766	2.7 mm
Total Mass	ISO 8543	2478 g/m²
Nominal Total Pile Mass	ISO 2424	630 g/m²
Effective Pile Mass	ISO 8543	308 g/m²
Pile Density	ISO 8543	0.111 g/cm³
Total Recycled Content		53% (pre-consumer 53% post-consumer 0%)

Performance


Number of Tufts	ISO 1763	165,000/m² 42 per 10cm
Electrostatic Propensity	ISO 6356	≤ 2.0 kv (Stroll Test)
Use Classification	EN 1307	33 Commercial Heavy
Luxury Class	EN 1307	LC1
Dimensional Stability	EN 986	≤ 0.2%
Impact Sound Insulation	ISO 10140	26 Db
Sound Absorption Classification	ISO 354/11654	0.20 Aw Class E
Thermal Resistance m² K/W	ISO 8302	0.075 M² K/W Tog 0.75
Dry Slip Resistance	ISO 13893	Pass / No Pulled Loops
Colour Fastness To Light	ISO 105-B02	>6
Flammability	EN 13501-1	Bfl-S1 (Adhered Testing)
Castor Chair	EN 985	≥2.4 Continuous USe

Lifetime Commercial Limited subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.


Recommended Installation Method




Monolithic




Quarter Turn



Brick



Ashlar



Random





26 dB

Coordinating Products

Carpet Tile: **Stone Comfortworx® Tile, Fragment Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Stone Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Stone Taskworx® Tile, Formation Colours Ecoworx S® Tile, Fragment Colours Ecoworx S® Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecoworx S® Tile, Stone Ecoworx S® Tile, Formation Taskworx® Tile, Formation Ecoworx S® Tile, Stone Colours Taskworx® Tile**

Material Health & Environmental Certifications















Certifications below apply exclusively to the carpet tile rug itself and not the LokWorx Tabs adhesive

Country of Origin**	United Kingdom
BREEAM Contribution Credit	Certificate of Approval Schools/Offices/Health/Industrial Shed Retail

Memberships

WGBC Framework	WGBC Framework
UKGBC	UKGBC
Emirates Green Building Council	Emirates Green Building Council
Chemsec	Chemsec

Light Reflectance Value

 <div>Oatmeal 04111 LRV 31.9 L* 63.25</div>	 <div>Brushed Gold 04210 LRV 24.6 L* 56.69</div>	 <div>Mineral 04327 LRV 22.9 L* 54.94</div>	 <div>Racing Green 04334 LRV 6.2 L* 29.9</div>	 <div>Sage 04375 LRV 22.3 L* 54.39</div>	 <div>Midnight Sage 04376 LRV 7.5 L* 32.97</div>
 <div>Sky 04411 LRV 24.9 L* 56.96</div>	 <div>Midnight Sky 04412 LRV 9.6 L* 37.08</div>	 <div>Steel Blue 04447</div>	 <div>Denim 04486 LRV 10 L* 37.8</div>	 <div>Apricot 04675 LRV 23.4 L* 55.49</div>	 <div>Power Pink 04800 LRV 30.1 L* 61.73</div>
 <div>Copper 04865 LRV 18.9 L* 50.61</div>	 <div>Rosewood 04870 LRV 18.8 L* 50.47</div>				

Additional Information

lifetime commercial limited

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

