

Gegevens

Steken	ISO 1763	165,000/m² 42 per 10cm
Elektrostatische Weerstand	ISO 6356	≤ 2.0 kv (Stroll Test)
Gebruik Classificatie	EN 1307	33 Commercial Heavy
Luxeklasse	EN 1307	LC1
Dimensionale Stabiliteit	EN 986	≤ 0.2%
Contactgeluidsisolatie	ISO 10140	26 Db
Geluidsabsorptieclassificatie	ISO 354/11654	0.20 Aw Class E
Warmteweerstand m² K/w	ISO 8302	0.075 M² K/W Tog 0.75
Weerstand Tegen Droog Uitglijden	ISO 13893	Pass / No Pulled Loops
Kleurvastheid Voor Licht	ISO 105-B02	>6
Ontvlambaarheid	EN 13501-1	Bfl-S1 (Adhered Testing)
Stoel Met Wieljies	EN 985	≥2.4 Continuous Use


Aanbevolen Installatiemethode




Monolithic




Quarter Turn



Brick



Ashlar



Random

Kenmerken + Certificeringen

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

land van herkomst
BREEAM Contribution Credits

Verenigd Koninkrijk
Certificate of Approval
Schools/Offices/Health/Industrial Shed
Retail



26 dB

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company
July 18, 2025

1 of 3

Coördinerende Producten

Carpet Tile: **Stone Comfortworx® Tile, Fragment Comfortworx® Tile, Formation Colours Comfortworx® Tile, Fragment Colours Comfortworx® Tile, Stone Colours Comfortworx® Tile, Formation Comfortworx® Tile, Fragment Taskworx® Tile, Stone Taskworx® Tile, Formation Colours Ecoworx S® Tile, Fragment Colours Ecoworx S® Tile, Formation Colours Taskworx® Tile, Fragment Colours Taskworx® Tile, Fragment Ecoworx S® Tile, Stone Ecoworx S® Tile, Formation Taskworx® Tile, Formation Ecoworx S® Tile, Stone Colours Taskworx® Tile**

Memberships

- WGBC Framework

UKGBC

Emirates Green Building Council














Chemsec
- WGBC Framework

UKGBC

Emirates Green Building Council

Chemsec

Lichtreflectiewaarde

 <div>Oatmeal 04111 LRV 31.9 L* 63.25</div>	 <div>Brushed Gold 04210 LRV 24.6 L* 56.69</div>	 <div>Mineral 04327 LRV 22.9 L* 54.94</div>	 <div>Racing Green 04334 LRV 6.2 L* 29.9</div>	 <div>Sage 04375 LRV 22.3 L* 54.39</div>	 <div>Midnight Sage 04376 LRV 7.5 L* 32.97</div>
 <div>Sky 04411 LRV 24.9 L* 56.96</div>	 <div>Midnight Sky 04412 LRV 9.6 L* 37.08</div>	<div>Steel Blue 04447</div>	 <div>Denim 04486 LRV 10 L* 37.8</div>	 <div>Apricot 04675 LRV 23.4 L* 55.49</div>	 <div>Power Pink 04800 LRV 30.1 L* 61.73</div>
 <div>Copper 04865 LRV 18.9 L* 50.61</div>	 <div>Rosewood 04870 LRV 18.8 L* 50.47</div>				

Aanvullende Informatie

lifetime commercial limited

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

