

Understated Ecoworx S® Tile


Numéro Du Style	5T647	
Collection	Creative Connections	
Type De Produit	Dalles De Moquette	
Construction	Standard	Data + Performance
Type De Fabrication	ISO 2424	tufted 1/10" 39.4 per 10cm
Construction	ISO 2424	Tufté Structuré Bouclé à Motif
Méthode De Coloration	EN 994	100% Solution Teinte
Dimensions Du Produit	EN 994	50 cm x 50 cm 20 tiles (5 m²) per box
Sous-couche Primaire	ISO 2424	Pet Non-Woven
Sous-couche Secondaire	ISO 2424	Ecoworx S® Polyolefin Plastomer
Epaisseur Du Velours	ISO 1765	7.0 mm
Épaisseur Du Velours Fini	ISO 1766	2.3 mm
Poids Total	ISO 8543	2984 g/m²
Poids Tufté	ISO 2424	762 g/m²
Poids Du Velours Utile	ISO 8543	291 g/m²
Densité Du Velours	ISO 8543	0.126 g/cm³
Contenu Recyclé Total		55% (pre-consumer 55% post-consumer 0%)

Données


Points	ISO 1763	124,000/m² 31.5 per 10cm
Propension Electrostatique	ISO 6356	≤ 2.0 kv (Stroll Test)
Classification d'Utilisation	EN 1307	33 Commercial Heavy
Classification Luxe	EN 1307	LC1
Stabilité Dimensionnelle	EN 986	≤ 0.2%
Isolation Acoustique	ISO 10140	26 Db
Classification d'Absorption Sonore	ISO 354/11654	0.15 αW Class E
Résistance Thermique m² K/w	ISO 8302	0.087 M² K/W Tog 0.87
Dry Slip Resistance	ISO 13893	
Résistance De La Couleur À La Lumière	ISO 105-B02	>6
Inflammabilité	EN 13501-1	Bfl-S1 (Adhered Testing)
Chaise À Roulette	EN 985	≥2.4 Intensive USe

Durée De Vie Commerciale Limitée subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.


Méthodes d'Installation Conseillées




Quarter Turn




Brick




Ashlar



Random





26 dB0.15 αw

Coordination Des Produits

Carpet Tile: **Interlaced Comfortworx® Tile, Interlaced Taskworx® Tile, Interlaced Ecoworx S® Tile**

Attributs + Certifications

Certifications Below Apply Exclusively To The Carpet Tile Rug Itself And Not The Lokworx Tabs Adhesive

Certification Cradle to Cradle™ (C2C)

Déclaration environnementale de produit (EPD)

Embodied Carbon (Cradle to Gate)

Life-Cycle Carbon Emissions

garantie environnementale

pays d'origine

BREEAM Contribution Credit

Silver Level (Version 3.1)

Certifié Par Un Organisme Tiers Conformément Aux Normes ISO 14044, ISO 14025 & EN15804

4.35 kg CO₂/m²

Carbon Neutral

Take Back Policy Offered For All Ecoworx S® Products

United Kingdom

Certificate of Approval

Schools/Offices/Health/Industrial Shed

Retail

Well V2 Contribution Credit

X08 Réduction des matières dangereuses Partie 1 : Optimiser la limitation des matières dangereuses – 1 pt

C2C Silver Level (Version 3.1)

X10 Réduction des composés volatils Partie 1 (A) : Optimisation de la gestion des composés organiques volatils (COV) – 1 pt

C2C Silver Level (Version 3.1)

X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

M1> Emissions Class For Building Material

X13 Précaution accrue à l'égard des matériaux Partie 1 : Choisir des matériaux optimisés – max 2 pts

C2C Silver Level (Version 3.1)

X14 Transparence des matériaux Partie 1 : Promouvoir l'optimisation de la divulgation des composants – max 2 pts

C2C Silver Level (Version 3.1)

Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 1: Material Ingredient Reporting

C2C Silver Level (Version 3.1)

MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 2: Material Ingredient Optimization

C2C Silver Level (Version 3.1)

Memberships

WGBC Framework

WGBC Framework

UKGBC

UKGBC













Emirates Green Building Council

Emirates Green Building Council

Chemsec

Chemsec

Indice De Réflexion Lumineuse

					
Refined - Butterscotch 47210 LRV 30.7 L* 62.27	Pure - Mineral 47327 LRV 42.0 L* 70.90	Classic - Sage 47375 LRV 21.9 L* 53.96	Pure - Sky 47411 LRV 40.5 L* 69.81	Classic - Slate Blue 47447 LRV 21.5 L* 53.54	Mellow - Storm Cloud 47485 LRV 24.7 L* 56.75
					
Mellow - Medallion 47668 LRV 22.0 L* 54.01	Classic - Dusty Apricot 47675 LRV 21.7 L* 53.73	Pure - Bisque 47676 LRV 39.7 L* 69.25	Refined - Walnut 47760 LRV 30.9 L* 62.39	Refined - Powder Pink 47800 LRV 31.9 L* 63.28	Mellow - Rose 47870 LRV 20.1 L* 51.93

Informations Supplémentaires

**Manufactured in ISO 9001 certified facility. Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

[durée de vie commerciale limitée](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.



Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company
July 12, 2025

3 of 3