

Solid

Product Type	Broadloom	
Style Number	5A137	
Construction	Pattern Cut/Loop	
Fiber	Nylon	
Primary Backing	Synthetic	
Secondary Backing	Classicbac®	
Protective Treatments	SSP® Shaw Soil Protection	
Recommended Adhesive	H1000, H1200 or H3800	
	metric	u.s.
Product Size	3.66 m	12 ft
Gauge	31.5 per 10 cm	1/8 in
Stitches	55.0 per 10 cm	14.0 per in
Average Density	0.234 g/cm³	6330 oz/yd³
Kilotex	10.45	
Total Thickness	8.43 mm	0.332 in
Tufted Weight	1085 g/m²	32 oz/yd²
Installation Pattern Repeat	1.27 cm X 1.27 cm	0.5 in X 0.5 in



Recommended Installation Method

Direct Glue, Double Glue, Stretch-In

Performance + Testing

Pill Test	Pass
Radiant Panel	Class I
NBS Smoke	Less Than 450
Electrostatic Propensity	Less Than 3.5 kv
CRI Green Label Plus (GLP)	GLP8878
ADA Compliance	>0.6, Meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes***

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

10 Year Commercial Limited








Material Health & Environmental Certifications

Cradle to Cradle Certified®	Silver Level (Version 3.1)
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
NSF 140	Gold
CRI Green Label Plus (GLP)	GLP8878
Environmental Guarantee*	Re[turn] Reclamation Program*   Pickup & Delivery Available
Total Recycled Content	<1% (Pre-Consumer <1%   Post-Consumer 0%)
Product Packaging	100% Recyclable
Country of Origin**	USA

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	C2C Silver Level (Version 3.1)
MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 2: Material Ingredient Optimization	C2C Silver Level (Version 3.1)
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	Certified

Available Colorways

					
Angora 37101	Almond 37103	Canvas 37104	Bare 37111	Malt 37121	Karat 37170
					
Luna 37274	Aerial View 37280	Autumn Fern 37334	Island 37436	Sirocco 37448	Tea 37480
					
Shadow 37496	Fathom 37498	Axis 37500	Bedrock 37504	Artifact 37511	Armor 37514




Gladiator 37522



Urban 37525




Sprout 37538



Verde 37543



Oxygen 37555



Polar 37575



Liquid 37590




Crocodile 37701



Pottery 37729



Lasso 37750



Balsamic 37758



Butte 37760




Morel 37761



Plum Brulee' 37777



Shiraz 37811




Koa 37823



Lava 37859



Social 37862



Mood 37911

## Additional Information

\* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](https://shawcontract.com/sustainability).

\*\*Meets or exceeds all local and national regulations in country of manufacture. (Manufactured in an ISO 9001 & ISO 14001 certified facility or equivalent)

\*\*\*This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.





PVC-Free