

## Escape

製品型	<b>Broadloom</b>
コレクション	<b>Off The Grid</b>
スタイルナンバー	<b>5A242</b>
建設	マルチレベルパターン/カットループ
ファイバ	エコソリューションQ®ナイロン
染色法	<b>100% 原液着色</b>
一次バックイング	<b>合成</b>
二次バックイング	<b>Ultraloc®</b>
保護治療	<b>SSP@shaw 土壌保護保証</b>
推奨接着剤	<b>1000 Broadloom 4 Gallon or 3800 Indoor Outdoor Broadloom 4 Gallon</b>

	u.s.	metric
商品のサイズ	<b>12 ft</b>	<b>3.66 m</b>
ゲージ	<b>1/10 in</b>	<b>39.4 per 10 cm</b>
ステッチ	<b>11.0 per in</b>	<b>43.0 per 10 cm</b>
完成した杭の厚さ	<b>0.169 in</b>	<b>4.29 mm</b>
平均密度	<b>5538 oz/yd³</b>	<b>0.205 g/cm³</b>
キロテックス		<b>13.48</b>
総厚	<b>0.347 in</b>	<b>8.81 mm</b>
房状の重量	<b>26 oz/yd²</b>	<b>881.5 g/m²</b>
インストールパターン リピート	<b>72 in w x 72 in l</b>	<b>1.83 m w x 1.83 m l</b>



## 推奨インストール方法

Direct Glue, Double Glue, Stretch-In

## データ + テスト

錠剤テスト	<b>Pass</b>
放射パネル (astm E648)	<b>Class I</b>
Nbs煙	<b>Less Than 450</b>
静電気の傾向	<b>Less Than 3.5 kv</b>
Cri Green Label Plus (glp)	<b>GLP2271</b>
Adaコンプライアンス	<b>&gt;0.6、ADA 歩行面およびアクセス可能ルート用推奨静摩擦係数の基準に合致***</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## 保証

生涯商用限定保証

コーディネート商品

Carpet Tile: **Seek Tile, Discover Tile, Beyond Tile, Expanse Tile**

Broadloom: **Beyond**

属性+認定

Health & Wellbeing

Material Ingredient Transparency

**Cradle to Cradle Certified® | シルバーレベル (バージョン 3.1)**  
**Health Product Declaration (HPD) | 1,000 ppm 開示**  
**NSF 140 | ゴールド**  
**CRI Green Label Plus (GLP) | GLP2271**

Indoor Air Quality

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Total Recycled Content

Product Packaging

**ISO14044、ISO14025 および EN15804 に基づく 第三者認証取得**  
**11.6 (based upon 27.41 oz face weight) kg CO<sub>2</sub>/m<sup>2</sup>**  
**<1% (Pre-Consumer <1% | Post-Consumer 0%)**  
**100% リサイクル可能**

Global Product Assessment

**CE Marking (EN 14041) | 第三者認証取得**  
**Environmental Guarantee\* | Re[turn] Reclamation Program\* | Pickup & Delivery Available**  
**Country of Origin\*\* | Imported**

Well V2 Contribution Credit

X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt

「C2C」シルバーレベル (バージョン3.1)

X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt

「C2C」シルバーレベル (バージョン3.1)

X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

**Green Label Plus Certification GLP2271**

X13 Enhanced Material Precaution Part 1: Select Optimized Materials Optimization – max 2 pts

「C2C」シルバーレベル (バージョン3.1)

X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization – max 2 pts

「C2C」シルバーレベル (バージョン3.1)

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築  
環境製品宣言-オプション1：環境製品宣言 (EPD)

**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**

MRクレジット：製品の開示と最適化の構築  
材料成分-オプション1：材料成分レポート

「C2C」シルバーレベル (バージョン3.1)


MRクレジット：製品の開示と最適化の構築  
材料成分-オプション2：材料成分の最適化

「C2C」シルバーレベル (バージョン3.1)

EQクレジット：低排出材料  
オプション1：製品カテゴリの計算

**Green Label Plus Certification: GLP2271**


## Available Colorways




Dune 15105  
LRV 19.1 | L\* 50.76



Canyon 15180  
LRV 13.9 | L\* 44.05



Moss 15326  
LRV 10 | L\* 37.93



Coast 15456  
LRV 4.8 | L\* 26.28




Vast 15505  
LRV 4.1 | L\* 24.05




Peak 15506  
LRV 19.8 | L\* 51.61




Slope 15518  
LRV 9.5 | L\* 36.85




Cliff 15530  
LRV 12.5 | L\* 42.06



Ridge 15580  
LRV 7.4 | L\* 32.75



Shore 15592  
LRV 12.3 | L\* 41.64



Summit 15597  
LRV 4.9 | L\* 26.33



Earth 15760  
LRV 6.7 | L\* 31.04

## 追加情報

\* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](https://shawcontract.com/sustainability).

\*\*Meets or exceeds all local and national regulations in country of manufacture. (Manufactured in an ISO 9001 & ISO 14001 certified facility or equivalent)

\*\*\*This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](https://shawcontract.com/testing) for more information.



**PVC-Free**

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

© 2025 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
July 2, 2025

3 of 3