

# ShawContract®

## Kennebunk

Product Type	<b>Broadloom</b>	
Collection	<b>Lush Life</b>	
Style Number	<b>5B092</b>	
Construction	<b>Cut Pile</b>	
Fiber	<b>Ecosolution Q® Nylon</b>	
Dye Method	<b>100% Dye Injection Print</b>	
Primary Backing	<b>Synthetic</b>	
Secondary Backing	<b>Classicbac®</b>	
Protective Treatments	<b>Srs® Stain Resistance Treatment</b>	
Recommended Adhesive	<b>1000 Broadloom 4 Gallon or 3800 Indoor Outdoor Broadloom 4 Gallon</b>	
	u.s.	metric
Product Size	<b>12 ft</b>	<b>3.66 m</b>
Gauge	<b>1/10 in</b>	<b>39.4 per 10 cm</b>
Stitches	<b>12.5 per in</b>	<b>49.0 per 10 cm</b>
Finished Pile Thickness	<b>0.257 in</b>	<b>6.53 mm</b>
Average Density	<b>5043 oz/yd<sup>3</sup></b>	<b>0.187 g/cm<sup>3</sup></b>
Kilotex		<b>11.75</b>
Total Thickness	<b>0.390 in</b>	<b>9.91 mm</b>
Tufted Weight	<b>36 oz/yd<sup>2</sup></b>	<b>1220.6 g/m<sup>2</sup></b>
Installation Pattern Repeat	<b>24" w x 24" l</b>	<b>60.96 cm w x 60.96 cm l</b>



### Recommended Installation Method

Direct Glue, Double Glue, Stretch-In

### Performance + Testing

Pill Test	<b>Pass</b>
Radiant Panel	<b>Class I</b>
NBS Smoke	<b>Less Than 450</b>
Electrostatic Propensity	<b>Less Than 3.5 kv</b>
ADA Compliance	<b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes***</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

### Warranties

20 Year Commercial Limited Warranty

### Material Health & Environmental Certifications

#### Climate Impact

Embodied Carbon (Cradle to Gate)

**12 kg CO<sub>2</sub>/m<sup>2</sup>**

Total Recycled Content

**<1% (Pre-Consumer <1% | Post-Consumer 0%)**

#### Global Product Assessment

**Country of Origin\*\* | USA**

## Coordinating Products

---

Broadloom: **Moritz, Cranford, Bellcourt**

## Available Colorways

---



Refined 92314



Ooh La La 92335



On The Town 92713



So Glam 92725



Panache 92761

## Additional Information

---

\*\*\*This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.